

ATUM

High-Shrink-Ratio, Adhesive-Lined Polyolefin Tubing

Product Facts

- 3:1 and 4:1 shrink ratios allow for connector-to-cable sealing
- Tubing environmentally seals and protects components and interconnections
- Medium wall provides increased mechanical protection
- The adhesive in ATUM tubing bonds to a wide variety of plastics, rubbers, and metals, including polyethylene, aluminum, steel, and copper
- RoHS compliant



Applications

Environmentally seals and protects a wide variety of electrical applications, including back end connector sealing, breakouts, and connector-to-cable transitions. High expansion ratio makes it possible to repair most damaged cable jackets without removing connectors.

Installation

Minimum shrink temperature: 80°C [176°F]
Minimum full recovery temperature: 110°C [230°F]

Operating Temperature Range

-55°C to 110°C
[-67°F to 230°F]

Specifications/Approvals

Series	UL** 	Military	Raychem
ATUM	E85381 600V, 110°C	AMS-DTL-23053/4,* Class 3	RW-2063 - Black RK-6024 - Colors and clear

*Formerly MIL-I-23053/4 and MIL-DTL-23053/4. Sizes 3/1, 6/2, 12/4, 24/8, and 40/13 only.

**Black only, except sizes 3/1 and 4/1.

Available in:	Americas	Europe	Asia Pacific
	■	■	■

ATUM (Continued)

Product Dimensions

Size	Inside Diameter		Recovered Wall Thickness**	
	Minimum Expanded as Supplied	Maximum Recovered After Heating	Total Wall After Heating	Adhesive Wall After Heating (Nominal)
3:1				
3/1	3.0 [0.118]	1.0 [0.039]	1.00 ± 0.28 [0.039 ± 0.010]	0.50 [0.020]
4.5/1.5	4.5 [0.177]	1.5 [0.059]	1.10 ± 0.25 [0.043 ± 0.011]	0.50 [0.020]
6/2	6.0 [0.236]	2.0 [0.079]	1.00 ± 0.28 [0.039 ± 0.010]	0.50 [0.020]
9/3	9.0 [0.354]	3.0 [0.118]	1.40 ± 0.28 [0.055 ± 0.010]	0.61 [0.024]
12/4	12.0 [0.472]	4.0 [0.157]	1.78 ± 0.38 [0.070 ± 0.015]	0.76 [0.030]
19/6	19.0 [0.748]	6.0 [0.236]	2.25 ± 0.55 [0.088 ± 0.022]	0.76 [0.030]
24/8	24.0 [0.940]	8.0 [0.315]	2.54 ± 0.55 [0.100 ± 0.022]	1.02 [0.040]
40/13	40.0 [1.570]	13.0 [0.512]	2.54 ± 0.55 [0.100 ± 0.022]	1.02 [0.040]
4:1				
4/1	4.0 [0.157]	1.0 [0.039]	1.00 ± 0.28 [0.039 ± 0.010]	0.50 [0.020]
8/2	8.0 [0.315]	2.0 [0.079]	1.00 ± 0.28 [0.039 ± 0.010]	0.50 [0.020]
12/3	12.0 [0.472]	3.0 [0.118]	1.40 ± 0.28 [0.055 ± 0.010]	0.61 [0.024]
16/4	16.0 [0.630]	4.0 [0.157]	1.78 ± 0.38 [0.070 ± 0.015]	0.76 [0.030]
24/6	24.0 [0.945]	6.0 [0.236]	2.25 ± 0.55 [0.088 ± 0.022]	0.76 [0.030]
32/8	32.0 [1.260]	8.0 [0.315]	2.54 ± 0.55 [0.100 ± 0.022]	1.02 [0.040]
52/13	52.0 [2.050]	13.0 [0.512]	2.54 ± 0.55 [0.100 ± 0.022]	1.02 [0.040]

**Wall thickness will be less if tubing recovery is restricted during shrinkage.

Ordering Information

Color	Standard	Black (-0)
	Nonstandard	Clear in 3:1 sizes only (-X, non-flame-retardant jacket); other colors available on request.
Size selection	Always order the largest size that will shrink snugly over the component to be covered. Special order sizes are available upon request.	
Standard packaging***	In 1.2-meter [4-foot] lengths or on spools.	
Ordering description****	Specify product name, size and color (for example, ATUM 8/2-0).	

***Only 1.2 meter [4-foot] lengths are standard in the Americas. ATUM tubing on spools is nonstandard.

****For supply to MIL spec., add -MS to ordering description.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity:

[ATUM-24/6-0-STK](#) [ATUM-24/8-0-MS-STK](#) [ATUM-24/8-0-STK](#) [ATUM-4/1-0-STK](#) [ATUM-52/13-0-STK](#) [ATUM-9/3-0-STK](#) [ATUM-6/2-0-STK](#) [ATUM-8/2-0-SP](#) [ATUM-40/13-0-SP](#) [ATUM-8/2-0-STK](#) [ATUM-40/13-0-STK](#) [ATUM-16/4-0-STK](#) [ATUM-12/3-0-STK](#) [ATUM-12/4-0-STK](#) [ATUM-19/6-0-STK](#) [ATUM-12/3-0-SP](#) [ATUM-16/4-0-SP](#) [ATUM-12/3-0-SP-CS6877](#) [ATUM-12/4-0-2.75IN](#) [ATUM-16/4-0-SP-CS6877](#) [ATUM-175/155-0-STK](#) [ATUM-24/6-0-100MM](#) [ATUM-24/6-0-SP-CS6877](#) [ATUM-32/8-0-SP-CS6877](#) [ATUM-40/13-0-MS-SP](#) [ATUM-52/13-0-SP-CS6877](#) [ATUM-6/2-0-2.125IN](#) [ATUM-32/8-0-STK](#) [ATUM-32/8-0-SP](#) [ATUM-12/4-X-STK](#) [ATUM-19/6-X-STK](#) [ATUM-24/8-X-STK](#) [ATUM-3/1-X-STK](#) [ATUM-6/2-X-STK](#) [ATUM-9/3-X-STK](#) [ATUM-3/1-0-STK](#) [ATUM-6/2-0-SP](#) [ATUM-24/8-0-SP](#) [ATUM-9/3-0-SP](#) [ATUM-6/2-0-MS-STK](#) [ATUM-40/13-0-MS-STK](#) [ATUM-3/1-0-MS-STK](#) [ATUM-12/4-0-MS-STK](#) [ATUM-12/4-0-SP](#) [ATUM-19/6-0-SP](#) [ATUM-24/6-0-SP](#) [ATUM-3/1-0-SP](#) [ATUM-4/1-0-SP](#) [ATUM-24/8-2-STK](#) [ATUM-52/13-0-SP](#) [ATUM-16/4-0-STK-CS7335](#) [ATUM-9/3-0-STK-CS6031](#) [ATUM-32/8-0-STK-CS7335](#) [ATUM-32/8-0-STK-CS6877](#) [ATUM-32/8-0-STK-CS7755](#) [ATUM-8/2-0-STK-CS7516](#) [ATUM-19/4-0-SP](#) [ATUM-4/1-0-STK-CS7335](#) [ATUM-8/2-0-STK-CS6877](#) [ATUM-12/3-0-STK-CS6877](#) [ATUM-12/3-0-STK-CS7335](#) [ATUM-8/2-0-STK-CS7335](#) [ATUM-19/6-X-SP](#) [ATUM-52/13-0-STK-CS7739](#) [ATUM-52/13-0-STK-CS8769](#) [ATUM-16/4-0-STK-CS6877](#) [ATUM-12/3-0-STK-CS7408](#) [ATUM-8/2-0-SP-CS7516](#) [ATUM-4.5/1.5-0-STK](#) [ATUM-6/2-2-SP](#) [ATUM-32/8-0-100MM](#) [ATUM-8/2-0-STK-CS7739](#) [ATUM-52/13-0-STK-CS6877](#) [ATUM-16/4-0-STK-CS7739](#) [ATUM-24/6-0-STK-CS6877](#) [ATUM-40/13-X-STK](#) [ATUM-24/6-0-STK-CS7335](#)