

DATASHEET

ITEM: 36006FR
WHEEL AS 100X40/40 BB SWIVEL FORK M40L +
BRAKE

WHEEL SERIE

Wheels with cast soft polyurethane coating 87 Sh.A on polyamide 6 center.
Wheel fitted with ball bearings.

FORK DESCRIPTION

M40 series, medium-heavy duty pressed steel forks, swivel with double ball races & 'water resistant' protections. Zincplated.


Trailing foot brake - total stop.

TECHNICAL DETAILS

Wheel diameter (D) 100 mm Tvre width (E) 40 mm Bore diameter (d) 15 mm Reference weight 1,677 kg Overall height (H) 137 mm Top plate outer dimensions (AxB) 105x85 mm Bolt hole spacing (axb) 76x55 mm (axb) 80x60 mm Bolt hole spacing Fixing bolt diameter (g) 8 mm Offset (F) 41 mm Fork width (U) 50 mm Load capacity 250 kg

Possible options :
Wheel replacement 35008
Brake FR





GENERAL INFORMATION / RECOMMENDATIONS AND WARNINGS

CC

The cited text and the complete catalogue in their most up-dated versions are available in our web-site www.lagspa.eu/web/downloads. The dimensions, descriptions, specifications and illustrations herein are indicative and subject to variations without notice. The fact that products are illustrated herein does not necessarily imply they are available from stock nor does it place us under any obligation to supply them. Tests carried out refer to the original products with original accessories: the replacement of one of the components with others of different manufacture might prevent the same results from being achieved and will automatically invalidate any guarantee. Please contact our technical service concerning any special application.