

SOLISTRAND | SOLISTRAND Budget

TE Internal #: 324599


Spade Tongue Terminal, 26 – 22 AWG, #2 / M2 Stud Size, 2.36 mm [.093 in] Stud Diameter, Closed Barrel, Flanged, Tin, Uninsulated,

SOLISTRAND Budget

View on TE.com >



Terminals & Splices > Spade Terminals



Spade Terminal Type: Spade Tongue Terminal

Wire Size: **202 – 810 CMA**

Stud Size: #2, M2

Features

Product Type Features

Troduct Type reatures	
Stud Size	#2, M2
Sealable	No
Wire Insulation Support Retention Type	Non-Insulation Support
Body Features	
Product Weight	.16 g
Contact Features	
Spade Terminal Type	Spade Tongue Terminal
Barrel Type	Closed
Terminal Orientation	Flanged
Terminal Plating Material	Tin
Mechanical Attachment	
Wire Insulation Support	Without
Dimensions	
Wire Size	202 – 810 CMA
Stud Diameter	2.36 mm[.093 in]



Tongue Thickness	.79 mm[.031 in]
Product Length	11.51 mm[.453 in]
Barrel Inside Diameter	.89 mm[.035 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	170 °C[338 °F]
Operation/Application	
Compatible With Wire Base Material	Copper
Compatible With Wire Plating Material	Tin
Industry Standards	
Government Qualified Terminal	No
Packaging Features	
Packaging Quantity	1000
Packaging Method	Loose Piece
Other	

Product Compliance

Line

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Budget

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these




limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | SOLISTRAND Budget







Customers Also Bought





Polyester Vertical PCB Header: 2.54


mm, Shrouded, MTA 100













TE Part #4-1423673-1 W51-A152A1-15=CKTBKR,THERM, ROC

Documents

Product Drawings

TERMINAL, BUDG SPD FLG 26-22 2

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_324599_K.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_324599_K.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_324599_K.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.