

VBL165R13S Datasheet

N-Channel 650V (D-S) Super Junction Power MOSFET

PRODUCT SUMMARY

V_{DS} (V) at T_J max.	650	
$R_{DS(on)}$ at 25 °C (Ω)	$V_{GS} = 10$ V	0.330

FEATURES

- Low figure-of-merit (FOM) $R_{on} \times Q_g$
- Low input capacitance (C_{iss})
- Reduced switching and conduction losses
- Ultra low gate charge (Q_g)
- Avalanche energy rated (UIS)




APPLICATIONS

- Server and telecom power supplies
- Switch mode power supplies (SMPS)
- Power factor correction power supplies (PFC)
- Lighting
 - High-intensity discharge (HID)
 - Fluorescent ballast lighting

TO-263



Top View



N-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS ($T_C = 25$ °C, unless otherwise noted)

PARAMETER			SYMBOL	LIMIT	UNIT
Drain-Source Voltage			V _{DS}	650	V
Gate-Source Voltage			V _{GS}	± 30	
Continuous Drain Current (T _J = 150 °C)	V _{GS} at 10 V	T _C = 25 °C	I _D	13	A
		T _C = 100 °C		8	
Pulsed Drain Current ^a			I _{DM}	39	
Linear Derating Factor				1.67	W/°C
Single Pulse Avalanche Energy ^b			E _{AS}	900	mJ
Maximum Power Dissipation			P _D	150	W
Operating Junction and Storage Temperature Range			T _J , T _{stg}	-55 to +150	°C
Drain-Source Voltage Slope	T _J = 125 °C		dV/dt	50	V/ns
Reverse Diode dV/dt ^d				4.5	
Soldering Recommendations (Peak Temperature) ^c	for 10 s			260	°C

Notes

- Repetitive rating; pulse width limited by maximum junction temperature.
- $V_{DD} = 100$ V, starting $T_J = 25$ °C, $L = 30$ mH, $R_g = 25$ Ω , $I_{AS} = 6$ A
- 1.6 mm from case.
- $I_{SD} \leq I_D$, $dI/dt = 100$ A/ μ s, starting $T_J = 25$ °C.

THERMAL RESISTANCE RATINGS

PARAMETER	SYMBOL	TYP.	MAX.	UNIT
Maximum Junction-to-Ambient	R_{thJA}	-	62	°C/W
Maximum Junction-to-Case (Drain)	R_{thJC}	-	0.7	

SPECIFICATIONS ($T_J = 25\text{ }^{\circ}\text{C}$, unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNIT
Static						
Drain-Source Breakdown Voltage	V_{DS}	$V_{GS} = 0\text{ V}$, $I_D = 250\text{ }\mu\text{A}$	650	-	-	V
V_{DS} Temperature Coefficient	$\Delta V_{DS}/T_J$	Reference to $25\text{ }^{\circ}\text{C}$, $I_D = 1\text{ mA}$	-	0.75	-	V/ $^{\circ}\text{C}$
Gate-Source Threshold Voltage (N)	$V_{GS(th)}$	$V_{DS} = V_{GS}$, $I_D = 250\text{ }\mu\text{A}$	3	-	5	V
Gate-Source Leakage	I_{GSS}	$V_{GS} = \pm 20\text{ V}$	-	-	± 100	nA
		$V_{GS} = \pm 30\text{ V}$	-	-	± 1	μA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 650\text{ V}$, $V_{GS} = 0\text{ V}$	-	-	1	μA
		$V_{DS} = 520\text{ V}$, $V_{GS} = 0\text{ V}$, $T_J = 125\text{ }^{\circ}\text{C}$	-	-	10	
Drain-Source On-State Resistance	$R_{DS(on)}$	$V_{GS} = 10\text{ V}$, $I_D = 4.5\text{ A}$	-	0.330	-	Ω
Forward Transconductance	g_{fs}	$V_{DS} = 30\text{ V}$, $I_D = 8\text{ A}$	-	5.6	-	S
Dynamic						
Input Capacitance	C_{iss}	$V_{GS} = 0\text{ V}$, $V_{DS} = 100\text{ V}$, $f = 1\text{ MHz}$	-	1900	-	pF
Output Capacitance	C_{oss}		-	80	-	
Reverse Transfer Capacitance	C_{rss}		-	4	-	
Effective Output Capacitance, Energy Related ^a	$C_{o(er)}$	$V_{DS} = 0\text{ V to } 520\text{ V}$, $V_{GS} = 0\text{ V}$	-	63	-	
Effective Output Capacitance, Time Related ^b	$C_{o(tr)}$		-	213	-	
Total Gate Charge	Q_g	$V_{GS} = 10\text{ V}$, $I_D = 8\text{ A}$, $V_{DS} = 520\text{ V}$	-	49	70	nC
Gate-Source Charge	Q_{gs}		-	15	-	
Gate-Drain Charge	Q_{gd}		-	19	-	
Turn-On Delay Time	$t_{d(on)}$	$V_{DD} = 520\text{ V}$, $I_D = 8\text{ A}$, $V_{GS} = 10\text{ V}$, $R_g = 9.1\text{ }\Omega$	-	18	25	ns
Rise Time	t_r		-	24	55	
Turn-Off Delay Time	$t_{d(off)}$		-	48	70	
Fall Time	t_f		-	25	40	
Gate Input Resistance	R_g	$f = 1\text{ MHz}$, open drain	-	0.8	-	Ω
Drain-Source Body Diode Characteristics						
Continuous Source-Drain Diode Current	I_S	MOSFET symbol showing the integral reverse p - n junction diode 	-	-	13	A
Pulsed Diode Forward Current	I_{SM}		-	-	39	
Diode Forward Voltage	V_{SD}	$T_J = 25\text{ }^{\circ}\text{C}$, $I_S = 8\text{ A}$, $V_{GS} = 0\text{ V}$	-	-	1.5	V
Reverse Recovery Time	t_{rr}	$T_J = 25\text{ }^{\circ}\text{C}$, $I_F = I_S = 8\text{ A}$, $dI/dt = 100\text{ A}/\mu\text{s}$, $V_R = 400\text{ V}$	-	475	-	ns
Reverse Recovery Charge	Q_{rr}		-	5.8	-	μC
Reverse Recovery Current	I_{RRM}		-	35	-	A

Notes

- a. $C_{oss(er)}$ is a fixed capacitance that gives the same energy as C_{oss} while V_{DS} is rising from 0 % to 80 % V_{DSS} .
 b. $C_{oss(tr)}$ is a fixed capacitance that gives the same charging time as C_{oss} while V_{DS} is rising from 0 % to 80 % V_{DSS} .

TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)



Fig. 1 - Typical Output Characteristics




Fig. 4 - Normalized On-Resistance vs. Temperature




Fig. 2 - Typical Output Characteristics




Fig. 5 - Typical Capacitance vs. Drain-to-Source Voltage




Fig. 3 - Typical Transfer Characteristics




Fig. 6 - Typical Gate Charge vs. Gate-to-Source Voltage




Fig. 7 - Typical Source-Drain Diode Forward Voltage




Fig. 9 - Maximum Drain Current vs. Case Temperature




Fig. 8 - Maximum Safe Operating Area




Fig. 10 - Temperature vs. Drain-to-Source Voltage




Fig. 11 - Normalized Thermal Transient Impedance, Junction-to-Case




Fig. 12 - Switching Time Test Circuit




Fig. 16 - Basic Gate Charge Waveform




Fig. 13 - Switching Time Waveforms




Fig. 14 - Unclamped Inductive Test Circuit




Fig. 15 - Unclamped Inductive Waveforms






Fig. 17 - Gate Charge Test Circuit



Note

a. $V_{GS} = 5 V$ for logic level devices

Fig. 18 - For N-Channel

Technical drawing of a mechanical part, showing multiple views and annotations:

- Front View (Top Left):** Shows the main profile of the part. Dimensions include E (total width), $L1$ (top flange width), D (height), H (total height), $L2$ (bottom flange width), and $2 \times b2$ (width of the bottom flange). Features include a central hole (1), two side holes (2, 3), and a bottom flange (4). Datum A is indicated by a triangle with the letter A.
- Side View (Top Right):** Shows the profile of the part. Dimensions include A (width), $c2$ (width of the bottom flange), and c (width of the base). A detail callout "Detail A" is shown with a dashed circle.
- Detail A (Bottom Right):** A magnified view of the bottom flange. It shows a gauge plane, a seating plane, and a lead tip. Dimensions include 0° to 8° (angle), $L3$ (width), $L4$ (width), and $A1$ (width). The detail is labeled "Detail 'A' Rotated 90° CW scale 8:1".
- Section B-B and C-C (Bottom Left):** A cross-section view showing the internal structure. Dimensions include $b1, b3$ (widths), $c1$ (height), and $(b, b2)$ (width). The section is labeled "Section B - B and C - C Scale: none".
- View A-A (Bottom Right):** A cross-section view showing the internal structure. Dimensions include E (total width), $D1$ (height), and $E1$ (width). The view is labeled "View A - A".
- Annotations:**
 - Lead tip:** A label pointing to the bottom flange.
 - Base metal:** A label pointing to the main body of the part.
 - Plating:** A label pointing to the top flange.
 - Seating plane:** A label pointing to the bottom flange.
 - Gauge plane:** A label pointing to the top flange.
 - Detail "A" Rotated 90° CW scale 8:1:** A label for the magnified view of the bottom flange.
- Feature Control Frames:**
 - Feature 1: $\varnothing 0.010 \text{ M A B}$
 - Feature 2: $\varnothing 0.010 \text{ M A B}$
 - Feature 3: $\varnothing 0.010 \text{ M A B}$
 - Feature 4: $\varnothing 0.010 \text{ M A B}$
 - Feature 5: $\varnothing 0.010 \text{ M A B}$
 - Feature 6: $\varnothing 0.010 \text{ M A B}$
 - Feature 7: $\varnothing 0.010 \text{ M A B}$
 - Feature 8: $\varnothing 0.010 \text{ M A B}$
 - Feature 9: $\varnothing 0.010 \text{ M A B}$
 - Feature 10: $\varnothing 0.010 \text{ M A B}$
 - Feature 11: $\varnothing 0.010 \text{ M A B}$
 - Feature 12: $\varnothing 0.010 \text{ M A B}$
 - Feature 13: $\varnothing 0.010 \text{ M A B}$
 - Feature 14: $\varnothing 0.010 \text{ M A B}$
 - Feature 15: $\varnothing 0.010 \text{ M A B}$
 - Feature 16: $\varnothing 0.010 \text{ M A B}$
 - Feature 17: $\varnothing 0.010 \text{ M A B}$
 - Feature 18: $\varnothing 0.010 \text{ M A B}$
 - Feature 19: $\varnothing 0.010 \text{ M A B}$
 - Feature 20: $\varnothing 0.010 \text{ M A B}$
 - Feature 21: $\varnothing 0.010 \text{ M A B}$
 - Feature 22: $\varnothing 0.010 \text{ M A B}$
 - Feature 23: $\varnothing 0.010 \text{ M A B}$
 - Feature 24: $\varnothing 0.010 \text{ M A B}$
 - Feature 25: $\varnothing 0.010 \text{ M A B}$
 - Feature 26: $\varnothing 0.010 \text{ M A B}$
 - Feature 27: $\varnothing 0.010 \text{ M A B}$
 - Feature 28: $\varnothing 0.010 \text{ M A B}$
 - Feature 29: $\varnothing 0.010 \text{ M A B}$
 - Feature 30: $\varnothing 0.010 \text{ M A B}$
 - Feature 31: $\varnothing 0.010 \text{ M A B}$
 - Feature 32: $\varnothing 0.010 \text{ M A B}$
 - Feature 33: $\varnothing 0.010 \text{ M A B}$
 - Feature 34: $\varnothing 0.010 \text{ M A B}$
 - Feature 35: $\varnothing 0.010 \text{ M A B}$
 - Feature 36: $\varnothing 0.010 \text{ M A B}$
 - Feature 37: $\varnothing 0.010 \text{ M A B}$
 - Feature 38: $\varnothing 0.010 \text{ M A B}$
 - Feature 39: $\varnothing 0.010 \text{ M A B}$
 - Feature 40: $\varnothing 0.010 \text{ M A B}$
 - Feature 41: $\varnothing 0.010 \text{ M A B}$
 - Feature 42: $\varnothing 0.010 \text{ M A B}$
 - Feature 43: $\varnothing 0.010 \text{ M A B}$
 - Feature 44: $\varnothing 0.010 \text{ M A B}$
 - Feature 45: $\varnothing 0.010 \text{ M A B}$
 - Feature 46: $\varnothing 0.010 \text{ M A B}$
 - Feature 47: $\varnothing 0.010 \text{ M A B}$
 - Feature 48: $\varnothing 0.010 \text{ M A B}$
 - Feature 49: $\varnothing 0.010 \text{ M A B}$
 - Feature 50: $\varnothing 0.010 \text{ M A B}$
 - Feature 51: $\varnothing 0.010 \text{ M A B}$
 - Feature 52: $\varnothing 0.010 \text{ M A B}$
 - Feature 53: $\varnothing 0.010 \text{ M A B}$
 - Feature 54: $\varnothing 0.010 \text{ M A B}$
 - Feature 55: $\varnothing 0.010 \text{ M A B}$
 - Feature 56: $\varnothing 0.010 \text{ M A B}$
 - Feature 57: $\varnothing 0.010 \text{ M A B}$
 - Feature 58: $\varnothing 0.010 \text{ M A B}$
 - Feature 59: $\varnothing 0.010 \text{ M A B}$
 - Feature 60: $\varnothing 0.010 \text{ M A B}$
 - Feature 61: $\varnothing 0.010 \text{ M A B}$
 - Feature 62: $\varnothing 0.010 \text{ M A B}$
 - Feature 63: $\varnothing 0.010 \text{ M A B}$
 - Feature 64: $\varnothing 0.010 \text{ M A B}$
 - Feature 65: $\varnothing 0.010 \text{ M A B}$
 - Feature 66: $\varnothing 0.010 \text{ M A B}$
 - Feature 67: $\varnothing 0.010 \text{ M A B}$
 - Feature 68: $\varnothing 0.010 \text{ M A B}$
 - Feature 69: $\varnothing 0.010 \text{ M A B}$
 - Feature 70: $\varnothing 0.010 \text{ M A B}$
 - Feature 71: $\varnothing 0.010 \text{ M A B}$
 - Feature 72: $\varnothing 0.010 \text{ M A B}$
 - Feature 73: $\varnothing 0.010 \text{ M A B}$
 - Feature 74: $\varnothing 0.010 \text{ M A B}$
 - Feature 75: $\varnothing 0.010 \text{ M A B}$
 - Feature 76: $\varnothing 0.010 \text{ M A B}$
 - Feature 77: $\varnothing 0.010 \text{ M A B}$
 - Feature 78: $\varnothing 0.010 \text{ M A B}$
 - Feature 79: $\varnothing 0.010 \text{ M A B}$
 - Feature 80: $\varnothing 0.010 \text{ M A B}$
 - Feature 81: $\varnothing 0.010 \text{ M A B}$
 - Feature 82: $\varnothing 0.010 \text{ M A B}$
 - Feature 83: $\varnothing 0.010 \text{ M A B}$
 - Feature 84: $\varnothing 0.010 \text{ M A B}$
 - Feature 85: $\varnothing 0.010 \text{ M A B}$
 - Feature 86: $\varnothing 0.010 \text{ M A B}$
 - Feature 87: $\varnothing 0.010 \text{ M A B}$
 - Feature 88: $\varnothing 0.010 \text{ M A B}$
 - Feature 89: $\varnothing 0.010 \text{ M A B}$
 - Feature 90: $\varnothing 0.010 \text{ M A B}$
 - Feature 91: $\varnothing 0.010 \text{ M A B}$
 - Feature 92: $\varnothing 0.010 \text{ M A B}$
 - Feature 93: $\varnothing 0.010 \text{ M A B}$
 - Feature 94: $\varnothing 0.010 \text{ M A B}$
 - Feature 95: $\varnothing 0.010 \text{ M A B}$
 - Feature 96: $\varnothing 0.010 \text{ M A B}$
 - Feature 97: $\varnothing 0.010 \text{ M A B}$
 - Feature 98: $\varnothing 0.010 \text{ M A B}$
 - Feature 99: $\varnothing 0.010 \text{ M A B}$
 - Feature 100: $\varnothing 0.010 \text{ M A B}$

	MILLIMETERS		INCHES	
DIM.	MIN.	MAX.	MIN.	MAX.
A	4.06	4.83	0.160	0.190
A1	0.00	0.25	0.000	0.010
b	0.51	0.99	0.020	0.039
b1	0.51	0.89	0.020	0.035
b2	1.14	1.78	0.045	0.070
b3	1.14	1.73	0.045	0.068
c	0.38	0.74	0.015	0.029
c1	0.38	0.58	0.015	0.023
c2	1.14	1.65	0.045	0.065
D	8.38	9.65	0.330	0.380

	MILLIMETERS		INCHES	
DIM.	MIN.	MAX.	MIN.	MAX.
D1	6.86	-	0.270	-
E	9.65	10.67	0.380	0.420
E1	6.22	-	0.245	-
e	2.54 BSC		0.100 BSC	
H	14.61	15.88	0.575	0.625
L	1.78	2.79	0.070	0.110
L1	-	1.65	-	0.066
L2	-	1.78	-	0.070
L3	0.25 BSC		0.010 BSC	
L4	4.78	5.28	0.188	0.208

1. Dimensioning and tolerancing per ASME Y14.5M-1994.
2. Dimensions are shown in millimeters (inches).
3. Dimension D and E do not include mold flash. Mold flash shall not exceed 0.127 mm (0.005") per side. These dimensions are measured at the outmost extremes of the plastic body at datum A.
4. Thermal PAD contour optional within dimension E, L1, D1 and E1.
5. Dimension b1 and c1 apply to base metal only.
6. Datum A and B to be determined at datum plane H.
7. Outline conforms to JEDEC outline to TO-263AB.

Disclaimer

All products due to improve reliability, function or design or for other reasons, product specifications and data are subject to change without notice.

Taiwan VBsemi Electronics Co., Ltd., branches, agents, employees, and all persons acting on its or their representatives (collectively, the "Taiwan VBsemi"), assumes no responsibility for any errors, inaccuracies or incomplete data contained in the table or any other any disclosure of any information related to the product.(www.VBsemi.com)

Taiwan VBsemi makes no guarantee, representation or warranty on the product for any particular purpose of any goods or continuous production. To the maximum extent permitted by applicable law on Taiwan VBsemi relinquished: (1) any application and all liability arising out of or use of any products; (2) any and all liability, including but not limited to special, consequential damages or incidental ; (3) any and all implied warranties, including a particular purpose, non-infringement and merchantability guarantee.

Statement on certain types of applications are based on knowledge of the product is often used in a typical application of the general product VBsemi Taiwan demand that the Taiwan VBsemi of. Statement on whether the product is suitable for a particular application is non-binding. It is the customer's responsibility to verify specific product features in the products described in the specification is appropriate for use in a particular application. Parameter data sheets and technical specifications can be provided may vary depending on the application and performance over time. All operating parameters, including typical parameters must be made by customer's technical experts validated for each customer application. Product specifications do not expand or modify Taiwan VBsemi purchasing terms and conditions, including but not limited to warranty herein.

Unless expressly stated in writing, Taiwan VBsemi products are not intended for use in medical, life saving, or life sustaining applications or any other application. Wherein VBsemi product failure could lead to personal injury or death, use or sale of products used in Taiwan VBsemi such applications using client did not express their own risk. Contact your authorized Taiwan VBsemi people who are related to product design applications and other terms and conditions in writing.

The information provided in this document and the company's products without a license, express or implied, by estoppel or otherwise, to any intellectual property rights granted to the VBsemi act or document. Product names and trademarks referred to herein are trademarks of their respective representatives will be all.

Material Category Policy

Taiwan VBsemi Electronics Co., Ltd., hereby certify that all of the products are determined to be RoHS compliant and meets the definition of restrictions under Directive of the European Parliament 2011/65 / EU, 2011 Nian. 6. 8 Ri Yue restrict the use of certain hazardous substances in electrical and electronic equipment (EEE) - modification, unless otherwise specified as inconsistent.(www.VBsemi.com)

Please note that some documents may still refer to Taiwan VBsemi RoHS Directive 2002/95 / EC. We confirm that all products identified as consistent with the Directive 2002/95 / EC European Directive 2011/65 /.

Taiwan VBsemi Electronics Co., Ltd. hereby certify that all of its products comply identified as halogen-free halogen-free standards required by the JEDEC JS709A. Please note that some Taiwanese VBsemi documents still refer to the definition of IEC 61249-2-21, and we are sure that all products conform to confirm compliance with IEC 61249-2-21 standard level JS709A.