



[Sitemap](#)
[Masthead](#)


 english

[HOME](#)
[PRODUCTS](#)
[CATALOGUE](#)
[COMPANY](#)
[LATEST NEWS](#)
[SERVICE](#)
[CONTACT](#)


 0 ARTICLES

You are here: [Products](#) » [Connectors f.con](#) » [PCB connectors](#) » [Male headers](#) » [SL 2 ... / SL 22 ...](#) »





▶ Heatsinks f.cool

▶ Cases f.case

▼ **Connectors f.con**

▶ Sockets
 ▶ PCB connectors

■ **Male headers**
 ■ Female headers
 ■ Direct female connector
 ■ Jumpers

 ▶ IDC-connectors
 ▶ D-Sub connectors
 ■ Brackets for PC
 ▶ Optoelectronics

Male headers

SL 2 ... / SL 22 ...

SL 22 124 6 S
two rows, □ 0.635 mm





[Features](#)
[Technical Drawing](#)
[Variants](#)
[Accessories / related products](#)

no. of contacts	6
contact material	CuSn alloy
surface contact / contact sleeve	Ni+≥0.2µm Au Ni+4...6µm Sn
surface of contact	selective gold-plated
volume resistivity	≤5 mΩ
nominal current	3 A
nominal voltage	250 VAC
test voltage	2000 V
material isolation body	PA4.6, GF
temperature range	-40 °C ... +163 °C -55 °C ... +105 °C
class of flammability	UL 94 V-0
insulation resistance	>10 ¹² Ω
connection type	soldering
version	standard
reflow solderable	yes

Fischer Elektronik GmbH & Co. KG
 Nottebohmstraße 28, D - 58511 Lüdenscheid
 ☎: +49 (0) 23 51 / 4 35 - 0, info@fischerelektronik.de







[Sitemap](#)
[Masthead](#)

<http://www.fischerelektronik.de/fcon/Connectors/PCBconnectors/301/Male%20headers/VA/SL221246S/index.xhtml>

1 / 1