# 9-1415001-1 ACTIVE

### SCHRACK | SCHRACK Miniature Relay PT

TE Internal #: 9-1415001-1

General Purpose Power Relay, Monostable, .759 W Coil, 777 ohm Coil Resistance, UL Coil Insulation Class F, SCHRACK Miniature Relay PT, Power Relays

View on TE.com >



Relays & Contactors > Relays > Power Relays









Relay Type: General Purpose Power Relay

Coil Magnetic System: Monostable

Coil Power Rating DC: .759 W

Coil Resistance: 777  $\Omega$ 

Coil Special Features: UL Coil Insulation Class F

### **Features**

### **Product Type Features**

Relay Type	General Purpose Power Relay
Configuration Features	
Coil Special Features	UL Coil Insulation Class F
Contact Arrangement	2 Form C DPDT-CO
Contact Number of Poles	2
Electrical Characteristics	
Insulation Initial Dielectric Between Open Contacts	1200 Vrms
Contact Limiting Making Current	24 A
Contact Limiting Short-Time Current	300 A
Insulation Initial Dielectric Between Adjacent Contacts	2500 Vrms
Insulation Initial Dielectric Between Contacts & Coil	1200 Vrms
Contact Limiting Breaking Current	12 A
Coil Power Rating DC	.759 W
Coil Resistance	777 Ω
Coil Voltage Rating	24 VDC
Contact Current Rating	12 A
Contact Switching Load (Min)	10mA @ 12V



Contact Switching Voltage (Max)	400 VAC
Contact Voltage Rating	240 VAC
Body Features	
Product Weight	30 g[1.058 oz]
Contact Features	
Contact Material	AgNi90/10
Termination Features	7 (9) (17 07 10
Relay Connection Type	Plug-In
	r iug-iri
Mechanical Attachment	
Product Mount Type	Socket
Dimensions	
Insulation Clearance Between Contact & Coil	3 mm
Insulation Creepage Between Contact & Coil	4 mm[.157 in]
Product Width	22.5 mm[.885 in]
Product Length	28 mm[1.1 in]
Product Height	29 mm[1.14 in]
Jsage Conditions	
Environmental Category of Protection	RTII
Environmental Ambient Temperature (Max)	70 °C[158 °F]
Operating Temperature Range	-40 – 70 °C
Operation/Application	
Current Type	DC
Indicator Type	LED
Coil Magnetic System	Monostable
Packaging Features	
Packaging Method	Carton & Tube
Other	
Length Class (Mechanical)	25 – 30 mm
Height Class (Mechanical)	25 – 30 mm
Coil Power Rating Class	.6 – .8 W
Width Class (Mechanical)	20 – 25 mm



### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Hand solderable with lead free solder

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts













TE Part # 1860000-1 PT7874P



TE Part # 4-1415033-1 PT78740



TE Part # 9-1415071-1 PT78730



TE Part # 3-1415043-1 PT78604



TE Part # 4-1415043-1 PT78600



TE Part # 5-1415034-1 PT78741



TE Part # 5-1415043-1 PT78602



TE Part # 2071566-3 PT78C2P



TE Part # 2071566-4 PT78A2P



TE Part # 2071566-6 PT78C02



TE Part # 1860100-1 PT7872P



Also in the Series | SCHRACK Miniature Relay PT



### Customers Also Bought



















TE Part #1825192-2 TT11DGPC9T1/404

TE Part #1649771-3 PCN-105D3MHF,000

### **Documents**

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_9-1415001-1\_O.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_9-1415001-1\_O.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_9-1415001-1\_O.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

Miniature Relay PT

English

### **Product Specifications**

**Definitions General Purpose Relays** 

English

### **Agency Approvals**

**VDE Certificate** 

English