

## Sensor/actuator cable - SAC-3P-M8MS/ 0,15-PUR/B-1L-Z - 1419618

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Sensor/actuator cable, 3-pos., PUR, halogen-free, RAL 7021 (black gray), straight M8 connector, A-coded, to valve connector B (10 mm), with 1 LED, connected to Z diode, cable length: 0.15 m

RoHS

### Key Commercial Data

|                        |                                                                                                       |
|------------------------|-------------------------------------------------------------------------------------------------------|
| Packing unit           | 1 pc                                                                                                  |
| Minimum order quantity | 50 pc                                                                                                 |
| GTIN                   | <br>4 055626 177526 |
| GTIN                   | 4055626177526                                                                                         |

### Technical data

#### General

|               |         |
|---------------|---------|
| Rated voltage | 24 V AC |
|               | 24 V DC |

#### Cable

|                                               |                                       |
|-----------------------------------------------|---------------------------------------|
| Cable type                                    | PUR halogen-free black                |
| Cable type (abbreviation)                     | PUR                                   |
| Cable abbreviation                            | Li9Y11Y                               |
| UL AWM style                                  | 20549                                 |
| Conductor cross section                       | 3x 0.34 mm <sup>2</sup> (Signal line) |
| AWG signal line                               | 22                                    |
| Conductor structure signal line               | 42x 0.10 mm                           |
| Core diameter including insulation            | 1.27 mm ±0.02 mm (Signal line)        |
| Thickness, insulation                         | ≥ 0.21 mm (Core insulation)           |
|                                               | approx. 0.5 mm (Outer cable sheath)   |
| Wire colors                                   | brown, blue, black                    |
| Overall twist                                 | 3 wires, twisted                      |
| External sheath, color                        | black-gray RAL 7021                   |
| External cable diameter D                     | 3.85 mm ±0.15 mm                      |
| Smallest bending radius, fixed installation   | 19 mm                                 |
| Smallest bending radius, movable installation | 38 mm                                 |
| Number of bending cycles                      | 10000000                              |
| Bending radius                                | 44 mm                                 |

# Sensor/actuator cable - SAC-3P-M8MS/ 0,15-PUR/B-1L-Z - 1419618

## Technical data

### Cable

|                                 |                                                                     |
|---------------------------------|---------------------------------------------------------------------|
| Traversing path                 | 10 m                                                                |
| Traversing rate                 | 3 m/s                                                               |
| Acceleration                    | 10 m/s <sup>2</sup>                                                 |
| Cable weight                    | 23 kg/km                                                            |
| Outer sheath, material          | PUR                                                                 |
| Material conductor insulation   | PP                                                                  |
| Conductor material              | Bare Cu litz wires                                                  |
| Insulation resistance           | ≥ 100 GΩ*km (at 20 °C)                                              |
| Conductor resistance            | max. 58 Ω/km (at 20 °C)                                             |
| Nominal voltage, cable          | ≤ 300 V                                                             |
| Test voltage, cable             | ≥ 3000 V                                                            |
| Special properties              | Flexible cable conduit capable                                      |
|                                 | Silicone-free                                                       |
|                                 | Free of substances which would hinder coating with paint or varnish |
| Flame resistance                | in accordance with UL 758/1581 FT2                                  |
|                                 | DIN EN 60332-2-2 (20 s)                                             |
| Halogen-free                    | in accordance with DIN VDE 0472 part 815                            |
| Resistance to oil               | in accordance with DIN EN 60811-2-1                                 |
| Other resistance                | Highly resistant to acids, alkaline solutions and solvents          |
|                                 | hydrolysis and microbe resistant                                    |
|                                 | partly UV-resistant in accordance with DIN EN ISO 4892-2-A          |
| Ambient temperature (operation) | -40 °C ... 80 °C (cable, fixed installation)                        |
|                                 | -25 °C ... 80 °C (cable, flexible installation)                     |

### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| REACH SVHC | Lead 7439-92-1                                                                                      |
| China RoHS | Environmentally Friendly Use Period = 50                                                            |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Approvals

### Approvals

Approvals

CSAus

Ex Approvals

### Approval details

## Sensor/actuator cable - SAC-3P-M8MS/ 0,15-PUR/B-1L-Z - 1419618

### Approvals

|                    |                                                                                   |                                                                                                                                         |       |
|--------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------|
| CSAus              |  | <a href="http://www.csagroup.org/services-industries/product-listing/">http://www.csagroup.org/services-industries/product-listing/</a> | 13631 |
| Nominal voltage UN |                                                                                   | 24 V                                                                                                                                    |       |
| Nominal current IN |                                                                                   | 4 A                                                                                                                                     |       |

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1419618](#)