

TC EXTENDER PT-IQ-1S - Surge protection plug



2702257

<https://www.phoenixcontact.com/pc/products/2702257>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Replaceable surge protection module, only for Ethernet extender TC EXTENDER 4001 ETH-1S (2702253), 1 SHDSL port, two-wire protection for floating SHDSL cables, two-level protective circuit

Commercial data

Item number	2702257
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	DNC442
Catalog page	Page 349 (C-6-2019)
GTIN	4055626057729
Weight per piece (including packing)	110.068 g
Weight per piece (excluding packing)	48.68 g
Customs tariff number	85363090
Country of origin	DE

TC EXTENDER PT-IQ-1S - Surge protection plug



2702257

<https://www.phoenixcontact.com/pc/products/2702257>

Technical data

Notes

Note on application

Note on application	Only for industrial use
---------------------	-------------------------

Product properties

Product type	Replacement plug
IEC test classification	B1
	C1
	C2
	C3
	D1
Type	Male
Wire pairs per module	1

Data management status

Article revision	02
------------------	----

Insulation characteristics

Overvoltage category	II
Pollution degree	2

Electrical properties

Nominal voltage U_N	24 V DC
-----------------------	---------

Connection data

Connection method	pluggable
-------------------	-----------

Dimensions

Width	22 mm
Height	96 mm
Depth	80 mm

Protective circuit

Direction of action	Line-Line & Line-Earth Ground
Nominal discharge current I_n (8/20) μ s (line-line)	1 kA (C1, 300 pulses)
Nominal discharge current I_n (8/20) μ s (line-ground)	1 kA
Pulse discharge current I_{imp} (10/350) μ s (line-earth)	500 A (D1)
Nominal pulse current I_{an} (10/1000) μ s (line-line)	100 A (B1)
Nominal pulse current I_{an} (10/1000) μ s (line-earth)	100 A

Environmental and real-life conditions

Ambient conditions

TC EXTENDER PT-IQ-1S - Surge protection plug



2702257

<https://www.phoenixcontact.com/pc/products/2702257>

Degree of protection	IP20
----------------------	------

Approvals

Conformity/Approvals

Noxious gas test	ISA-S71.04-1985 G3 Harsh Group A
------------------	----------------------------------

Standards and regulations

Standards/specifications	IEC 61643-21
Standards/specifications	IEC 60664-1

Mounting

Mounting type	Pluggable (slot)
Thread type	()


TC EXTENDER PT-IQ-1S - Surge protection plug

2702257

<https://www.phoenixcontact.com/pc/products/2702257>


Drawings

Schematic diagram



Function elements

Schematic diagram



Replacement of protection module

TC EXTENDER PT-IQ-1S - Surge protection plug



2702257

<https://www.phoenixcontact.com/pc/products/2702257>

Classifications

ECLASS

ECLASS-11.0	27130807
ECLASS-13.0	27171592

ETIM

ETIM 9.0	EC002497
----------	----------

UNSPSC

UNSPSC 21.0	39121600
-------------	----------

TC EXTENDER PT-IQ-1S - Surge protection plug



2702257

<https://www.phoenixcontact.com/pc/products/2702257>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	7(c)-I
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

TC EXTENDER PT-IQ-1S - Surge protection plug



2702257

<https://www.phoenixcontact.com/pc/products/2702257>

Mandatory accessories

TC EXTENDER 4001 ETH-1S - Ethernet extenders

2702253

<https://www.phoenixcontact.com/pc/products/2702253>



Managed Ethernet extender, point-to-point connections, data rates up to 15.3 Mbps, distances of up to 20 km on in-house copper cables, replaceable surge protection, 1 SHDSL port, 1 LAN port, diagnostics via Ethernet

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com