

You are here: [Products](#) » [Heatsinks f.cool](#) » [Profile heatsinks and fluid coolers](#) » [Extruded heatsinks for PCB mounting](#) » [SK 138 ...](#) » [SK 138](#)



▼ Heatsinks f.cool

- ▼ Profile heatsinks and fluid coolers
  - Standard extruded heatsinks
  - Extruded heatsinks for lock-in retaining spring
  - [Extruded heatsinks for PCB mounting](#)
  - Extruded heatsinks for DC/DC converter
  - Retaining springs for transistors
  - U-Extruded heatsinks
  - Die-cast heatsinks
  - Fin coolers
  - Fluid coolers
  - Aluminium flat-, quadrangular-, angled-, U- and T-profiles
- ▶ Heatsinks and active heatsinks for processors
- ▶ Board Level heatsinks
- ▶ Cooling aggregates
- ▶ Accessories for electronic components

▶ Cases f.case

▶ Connectors f.con

Extruded heatsinks for PCB mounting

SK 138 ...

SK 138 84 SA

50 x 28 mm, for use on Euro cards, profile thread

Data sheet

add to request



Features

Technical Drawing

Service

way of fixation	transistor screw mounting
width B	50 mm
height	28 mm
plate thickness	8 mm
length	84 mm
thermal resistance $R_{th}$	6.7 - 3.4 K/W
surface	black anodised