




E-NETTR

10/100 Base-T single port transformer Module

P/N:H1616G

- * Designed to meet IEEE802.3u requirement
- * Lead-Free & Designed to meet RoHS requirement
- * Designed to meet IR 255°C peak Requirement.
- * Low Profile package for CardBus Application
- * Operating Temperature Range -0°C to +70°C
- * Storage temperature range:0°C to +70°C




Electrical Specifications@25 ° C

Part Number	Turn Ratio (±3%)	OCL(uH Min) @ 100KHz/0.1V with 0mADC Bias	L.L (uH Max)	C _{w/w} (pF Max)	DCR (Ω Max)	Hi-Pot (Vrms MIN)
H1616G	1CT:1CT	350	0.5	28	1.1	AC1500V 1mA

Continue


Part Number	Insertion Loss 0.3~100MHZ (dB Max)	Return Loss (dB Min)				Cross Talk (dB Min)		DCMR (dB Min)		
		0.3-30MHz	60MHz	80MHz	100MHz	0.3-60MHz	60-100MHz	0.3-30MHz	60MHz	100MHz
H1616G	-1.1	-18	-14	-12	-10	-40	-35	-42	-37	-33

Mechanical



Unless:mm[inch] Tolerances: xx.xo ± 0.25[0.010]
o.xx ± 0.05[0.002]

Schematics



东莞市祥星电子有限公司

地址: 东莞市石碣镇横滘科技中路第三工业区 Miss Xie: 13549396638

TEL:0769-86384669 FAX:0769-81813600 Http://www.e-nettr.com xingguang@e-nettr.com