




Technical Data

Self-laminating labels, laser printer
Helatag 1104 (White-Transparent)

22.01.2024

TAG132LA4-1104-WHCL

Article Number 594-41104



Material: Type 1104, Polyester, white transparent, self-laminating (1104)

Colour: White (WH), Transparent (CL)

Operating Temperature : -40 °C to +150 °C

Curing Temperature: from +10 °C

Bundle Ø min.: 3.80 mm

Bundle Diameter max (metric): 7.60 mm

Self adhesive (Yes/No): Yes

Width (W): 20.32 mm

Height (H): 12.70 mm

Height (H2): 36.50 mm

Width of Liner (WL): 210.00 mm

Labels per Row: 9 pcs.

Labels per Sheet: 63 pcs.

Thickness of Foil: 25 µm

Thickness of Adhesive (TA) nom.: 21.5 µm

Flammability: UL 94 V0

Test Method
ASTM D3652

Adhesive: Acrylic

Initial tack: 280 g/cm²

Peel strength: 100 h

ASTM D2979

FINAT FTM 8

We assume no responsibility that the Product will be used for the intended purpose, this is beyond our control. It's up to the customer to check the suitability for a specific application by means of tests. Technical changes and errors reserved




Technical Data

22.01.2024

Self-laminating labels, laser printer
Helatag 1104 (White-Transparent)

UL-File Number:	MH61377
Print Method:	laser print
Shelf Life:	Minimum 1 year upon receipt / maximal 2 years after production date.
Storage Temperature:	+21 °C
Storage conditions:	50% relative humidity., The storage in the original packaging is recommended., Please avoid warehousing under impacts such as high humidity, heat and coldness.
Application Method:	The functionality and durability of the labels can be negatively affected if improperly processed or applied. All surfaces to be bonded must be clean, dry as well as free from dust and grease. Avoid touching the adhesive surface of the label as this could impair the application performance.



We assume no responsibility that the Product will be used for the intended purpose, this is beyond our control. It's up to the customer to check the suitability for a specific application by means of tests. Technical changes and errors reserved