CSTA263NN00440020000 V ACTIVE



TE Internal #: CSA263N00440020000

Cable-to-Cable, 6 Position, Power & Signal, Cable Mount (Free-Hanging), Electrodeposited Nickel, Zinc Alloy, PA66, Standard

Circular Connectors

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors











Connector System: Cable-to-Cable

Connector Mounting Type: Cable Mount (Free-Hanging)

Number of Positions: 6

Sealable: No

Circuit Application: Power & Signal

Features

Product Type Features

| Connector System Cable-to-Cable Sealable No | Product Type | Housing Assembly |
|--|-------------------------|------------------|
| Sealable | Connector System | Cable-to-Cable |
| | Sealable | No |
| Circular Connector Type Plug | Circular Connector Type | Plug |
| Shell Type Metal | Shell Type | Metal |

Configuration Features

| Number of Positions | 6 |
|----------------------------|----|
| Number of Power Positions | 4 |
| Number of Signal Positions | 2 |
| Contacts Preloaded | No |

Electrical Characteristics

| Operating Voltage | 250 VAC, 630 VAC | |
|-------------------|------------------|--|
|-------------------|------------------|--|

Body Features

| Environmental Protection Type | Sealed | |
|-------------------------------|--------|--|
|-------------------------------|--------|--|



| Environmental Protection | IP67 |
|---|----------------------------------|
| Shell Plating Material | Electrodeposited Nickel |
| Shell Base Material | Zinc Alloy |
| Circular Connector Insulation Material Type | PA66 |
| Mechanical Attachment | |
| Mating Retention Type | Speedtec (Triple Start Threaded) |
| Mating Alignment | With |
| Connector Mounting Type | Cable Mount (Free-Hanging) |
| Mating Retention | With |
| Housing Features | |
| Circular Connector Shell Size | 40 |
| Alignment Keyed | 0° |
| Dimensions | |
| Cable Diameter Range | 9 – 16 mm[.35 – .63 in] |
| Usage Conditions | |
| IP Water Sealing Level | IP67 |
| Operating Temperature Range | -20 – 130 °C[-4 – 266 °F] |
| Operation/Application | |
| Durability Rating | 500 Cycles |
| Circuit Application | Power & Signal |
| Shielded | Yes |
| Industry Standards | |
| UL Flammability Rating | UL 94V-0 |
| | |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant with Exemptions |
|---|--|
| EU ELV Directive 2000/53/EC | Compliant with Exemptions |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2024 (241) |

Cable-to-Cable, 6 Position, Power & Signal, Cable Mount (Free-Hanging), Electrodeposited Nickel, Zinc Alloy, PA66, Standard Circular Connectors



Candidate List Declared Against: JAN 2024 (240)

SVHC > Threshold:

Pb (3.5% in Component Part)

Article Safe Usage Statements:

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content

Not Yet Reviewed for halogen content

Solder Process Capability

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # CKA267N00440026000 940 EXTENSION, SPEEDTEC



TE Part # C0-0004-000-000
POSITIONING INSERT FOR 2 MM
CONTACTS





TE Part # C0-0201-000-P00 CRIMPING TOOL MID-SIZE

TE Part # C0-0236-000-P00
DIGITAL CRIMPING TOOL, MID SIZE

TE Part # C0-0008-000-P00 CRIMPING TOOL LARGE





Customers Also Bought





















Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_CSA263N00440020000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_CSA263N00440020000_A.3d_igs.zip

English

Cable-to-Cable, 6 Position, Power & Signal, Cable Mount (Free-Hanging), Electrodeposited Nickel, Zinc Alloy, PA66, Standard Circular Connectors



Customer View Model

ENG_CVM_CVM_CSA263N00440020000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

940 Plug CSA263N00440020000

English

CSA263N00440020000

English

fuer Datenblaetter, die online konfigurierbar sind

German

Product Specifications

German