



Connectors > PCB Connectors > PCB Headers & Receptacles



Connector System: **Wire-to-Board**

Number of Positions: **4**

Number of Rows: **2**

Centerline (Pitch): **16 mm [.63 in]**

PCB Mount Orientation: **Horizontal**

Features

Product Type Features

Connector System	Wire-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
PCB Connector Assembly Type	PCB Mount Header

Configuration Features

Number of Positions	4
Number of Rows	2
PCB Mount Orientation	Horizontal

Body Features

Primary Product Color	Black
-----------------------	-------

Contact Features

Contact Underplating Material Thickness	1.3 μm[51.18 μin]
Contact Mating Area Plating Material Thickness	2.54 μm[100 μin]
Contact Underplating Material	Nickel
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Silver



Contact Type	Pin
Contact Current Rating (Max)	65 A

Termination Features

Termination Method to PCB	Through Hole - Solder
---------------------------	-----------------------

Mechanical Attachment

Mating Alignment Type	Keyed
Mating Retention	With
PCB Mount Retention Type	Retention Leg
Connector Mounting Type	Board Mount
Mating Alignment	With
PCB Mount Alignment	Without
PCB Mount Retention	With

Housing Features

Housing Material	Polyester GF
Centerline (Pitch)	16 mm [.63 in]

Usage Conditions

Operating Temperature (Max)	105 °C [221 °F]
Operating Temperature Range	-55 – 105 °C [-67 – 221 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	9
Packaging Method	Box, Tube

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	



Current ECHA Candidate List: JUNE 2024 (241)
Candidate List Declared Against: JUNE 2024 (241)
Does not contain REACH SVHC

Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
-----------------	--

Solder Process Capability	Wave solder capable to 265°C
---------------------------	------------------------------

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # 2134055-1
DYNAMIC D7100 SOCKET HSG ASSY
4P XX



TE Part # CAT-D9934-A86
Contact: Component To Wire; 55-60A,
16-6 Wire Size

Also in the Series | Dynamic 7000 Series



Connector Contacts(10)



PCB Headers & Receptacles(1)



Wire-to-Board Connector Assemblies
& Housings(8)

Customers Also Bought



TE Part #HD14-3-96P
REC, 3P, GRY, N, THRD, 16

TE Part #W2S
WEDGE LOCK, 2P, PLG, ORG, STD, DT

TE Part #0460-202-16141
PIN, SOLID, SIZE 16, 16-20AWG, NI

TE Part #292156-3
CT RELAY HDR ASSY FREE HANGING

TE Part #2311768-2
AMPL REC, HD22, R/A, 26P, S/L

TE Part #2134055-1
DYNAMIC D7100 SOCKET HSG ASSY 4P XX

TE Part #0411-310-1605
EXT TOOL, SIZE 16, 16-18 AWG, T, LT BLU

TE Part #174934-1
070 MLC W-W CAP HSG 14P

TE Part #292254-3
CT RELAY HDR ASSY 3P NAT

Documents

Product Drawings

DYNAMIC D7100 HDR ASSY H 4P XX SQ

Japanese

CAD Files

Customer View Model

ENG_CVM_CVM_1981823-1_G.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1981823-1_G.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1981823-1_G.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



1-1773721-5_DYNAMIC_SERIES_QRG

English

Product Specifications

Product Specification

Japanese

Agency Approvals

TUV Certificate

English