

VOLTAGE RANGE: 12 KV
CURRENT: 5.0 mA
Features

- High speed switching
- High Current
- High surge resistivity for CRT discharge
- High reliability design
- High Voltage

Applications

- X light Power supply
- Laser
- Voltage doubler circuit
- Microwave emission power


Maximum Ratings and Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise specified

Characteristic	Symbols	2CL73		Units
Repetitive Peak Reverse Voltage	V_{RRM}	12		kV
Average Output Current $T_a=25^\circ\text{C}$, Resistive Load	I_o	5		mA _{peak}
Surge Current	I_{FSM}	0.5		A _{peak}
Maximum Forward Voltage Drop at 25°C , $I_F = I_{F(AV)}$	V_F	35		V
Maximum Reverse Current at 25°C at 100°C	V_{RRM}	2.0 5.0		uA uA
Maximum Reverse Recovery Time at 25°C	T_{rr}	100		nS
Junction Capacitance at 25°C , $V_R=0\text{V}$, $f=1\text{MHz}$	C_j	1.0		pF
Junction Temperature	T_j	125		°C
Allowable Operation Case Temperature	T_c	120		°C
Storage Temperature	T_{stg}	-40 to +125		°C

Outline Drawings : mm
