CSI-UFFR-100-UFFR ACTIVE

TE Internal #: CSI-UFFR-100-UFFR

MHF1 Cable Assembly, .1 – 1 m [.33 ft], Gray Cable, 3 GHz Operating Frequency, 50 ohm, FEP, 31 AWG, 1.13 mm [.044 in]

Diameter, UMCC GEN 1 Plug

View on TE.com >



Cable Assemblies > RF Cable Assemblies



Cable Assembly (End A): UMCC GEN 1 Plug
Cable Assembly (End B): UMCC GEN 1 Plug
Cable Assembly Length: .1 – 1 m [.33 ft]

Coax Cable Type: 1.13 mm

Impedance: 50Ω

Features

Product Type Features

Cable Assembly (End A)	UMCC GEN 1 Plug
Cable Assembly (End B)	UMCC GEN 1 Plug
Coax Cable Type	1.13 mm
Cable Assembly Type	MHF1
Configuration Features	
Number of Connectorized Ends	2

Electrical Characteristics

Impedance	50 Ω	

Body Features

Body Plating Material	Gold
Jacket Material	FEP
Cable Color	Gray

Contact Features

Dimensions

Outside Cable Diameter	1.13 mm[.044 in]
Wire Size	31 AWG



Usage Conditions

Operating Temperature Range	-40 – 90 °C[-40 – 194 °F]
Operation/Application	
Shielded	Yes
Operating Frequency	3 GHz
Other	
Dielectric Material	FEP
Cable Assembly Length	.1 – 1 m[.33 ft]

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Pb (4% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.



Compatible Parts









Customers Also Bought



TE Part #5787745-2 USB A R/A STAK ASSY THRU HOLE















Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_CSI-UFFR-100-UFFR_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_CSI-UFFR-100-UFFR_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_CSI-UFFR-100-UFFR_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

CSI-UFFR-100-UFFR

MHF1 Cable Assembly, .1 – 1 m [.33 ft], Gray Cable, 3 GHz Operating Frequency, 50 ohm, FEP, 31 AWG, 1.13 mm [.044 in] Diameter, UMCC GEN 1 Plug



CABLE ASSEMBLY, U.FL TO U.FL 1.13mm CBL

English