


REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A1	N/A		pin数表尺寸补充, 图面升级整理图面	2024.08.19	阿树
A2	N/A		产品总长尺寸变更	2024.11.26	阿树

■SPECIFICATIONS

- Voltage rating:250V AC/DC
- Current rating:2A AC/DC
- Withstanding Voltage:1500V AC/minute
- Temperature range:-25°C~+85°C
- Insulation resistance:≥1000MΩ
- Contact resistance:≤20mΩ

Poles	DIM		
	A	B	C
02	2.54	5.08	2.54
03	5.08	7.62	5.08
04	7.62	10.16	7.62
05	10.16	12.70	10.16
06	12.70	15.24	12.70
07	15.24	17.78	15.24
08	17.78	20.32	17.78
09	20.32	22.86	20.32
10	22.86	25.40	22.86
11	25.40	27.94	25.40
12	27.94	30.48	27.94
13	30.48	33.02	30.48
14	33.02	35.56	33.02
15	35.56	38.10	35.56
16	38.10	40.64	38.10
17	40.64	43.18	40.64
18	43.18	45.72	43.18
19	45.72	48.26	45.72
20	48.26	50.80	48.26



PART NO.:

X2954 W V-XX-NO SN
① ② ③ ④ ⑤ ⑥

- ①Series No
②Category:W-Wafer
③Welding Board Angle:V-Stright 180°
④Row No-Pin No:XX-02-20PIN
⑤Material:NO-Nylon66 UL94V-0
⑥Plating:SN-Tin Plated

X9254WV-XX-N0SN	Nylon66	Tin Plated	X9254H
PART NO	Material	Material(Brass)	Suitable XKB Housing

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERAUCES	



DESIGN
CHECKED
APPROVED

阿树

VIEW:
UNIT: mm/in
SIZE: A4

MODEL TYPE:
2.54mm Crimp Style Connector
PART NO.:
X9254WV-XX-N0SN
DWG NO.:

SCALE	PAGE	REVISION
N/A	1/1	A2

