

ZBF 17:UNBEDRUCKT - Zack Marker strip, flat



0815020

<https://www.phoenixcontact.com/us/products/0815020>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 17 mm, lettering field size: 17 x 5.2 mm, Number of individual labels: 5

Your advantages

- Unlabeled marking strips can be custom-labeled with a plotter or by hand
- Other pitches available on request
- The ZBF zack marker strip system with flat marker groove is a marking solution for modular terminal blocks and electronics modules
- The multi-section marking strips are easy to fit and can be easily separated if required

Commercial data

Item number	0815020
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BG05
Product key	BG2112
Catalog page	Page 131 (C-3-2019)
GTIN	4046356014229
Weight per piece (including packing)	0.737 g
Weight per piece (excluding packing)	0.737 g
Customs tariff number	39269097
Country of origin	DE

ZBF 17:UNBEDRUCKT - Zack Marker strip, flat



0815020

<https://www.phoenixcontact.com/us/products/0815020>

Technical data

Product properties

Product type	Terminal marking
Pitch	17 mm
Type	flat

Marking

Number of individual labels	5
Number of individual labels per row	5
Number of marker strips	10

Dimensions

Width	17 mm
Text field width	17.00 mm
Text field height	5.20 mm
Pitch	17 mm

Material specifications

Color	white
Material	PA
Flammability rating according to UL 94	V2
Components	free from silicone and halogen

Environmental and real-life conditions

UV resistance

Specification	ISO 4892-2:2013-03 (following)
---------------	--------------------------------

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-1):2011-07
	DIN EN 62208 (VDE 0660-511):2012-06 (in parts)

Ambient conditions

Ambient temperature (operation)	-40 °C ... 100 °C
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Mounting

Mounting type	snapped
---------------	---------

Drawings

Schematic diagram



ZBF 17:UNBEDRUCKT - Zack Marker strip, flat



0815020

<https://www.phoenixcontact.com/us/products/0815020>

Classifications

ECLASS

ECLASS-11.0	27281101
ECLASS-12.0	27281101
ECLASS-13.0	27281101

ETIM

ETIM 9.0	EC000761
----------	----------

UNSPSC

UNSPSC 21.0	39131500
-------------	----------

ZBF 17:UNBEDRUCKT - Zack Marker strip, flat



0815020

<https://www.phoenixcontact.com/us/products/0815020>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

ZBF 17:UNBEDRUCKT - Zack Marker strip, flat

0815020

<https://www.phoenixcontact.com/us/products/0815020>




Accessories

PLOTMARK - Marking plotter

0804499

<https://www.phoenixcontact.com/us/products/0804499>

Marking plotter for the entire portfolio of UC marking materials and materials in sheet and strip format.




CMS-P1-PLOTTER - Marking plotter

5144615

<https://www.phoenixcontact.com/us/products/5144615>

Marking plotter, weight: 8 kg, length: 0.66 m, width: 440 mm, height: 125 mm, color: silver



ZBF 17:UNBEDRUCKT - Zack Marker strip, flat



0815020

<https://www.phoenixcontact.com/us/products/0815020>

CMS-P1-M/ZBF - Magazine insert

5144709

<https://www.phoenixcontact.com/us/products/5144709>



Plastic magazines for CMS-P1-PLOTTER and PLOTMARK. For accommodating 26 flat zack marker strips or ZBN strips

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com