




The ECS-100X clock oscillator is fully compatible with TTL circuitry. The metal package with pin #7 case ground acts as shielding to minimize radiation.

FEATURES

- 10 TTL output load
- Low cost
- Wide frequency range
- Industry standard footprint
- Resistance weld package
- 3.3V operation (optional)
- PbFree/RoHS Compliant



PART NUMBERING GUIDE

PART NUMBER*	FREQUENCY STABILITY
ECS-100AX	±100 PPM
ECS-100BX	±50 PPM
ECS-100CX	±25 PPM

* Complete part number to include frequency, i.e. ECS-100AX-100 (100 = 10.000MHz)

OPERATING CONDITIONS/ELECTRICAL CHARACTERISTICS

PARAMETERS	FREQUENCY RANGE	CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
FREQUENCY RANGE (f_0)	1.000 ~ 150.000		1.000		150.000	MHz
OPERATING TEMP. RANGE (T_{OPR})	1.000 ~ 150.000		0		+70	°C
STORAGE TEMP. RANGE (T_{STG})	1.000 ~ 150.000		-55		+125	°C
FREQUENCY STABILITY	1.000 ~ 150.000	All conditions*	-100		+100	PPM
INPUT CURRENT (I_{DD})	1.000 ~ 7.999	max. load			15	mA
	8.000 ~ 23.999	max. load			30	mA
	24.000 ~ 69.999	max. load			70	mA
	70.000 ~ 150.000	max. load			80	mA
OUTPUT SYMMETRY	1.000 ~ 7.999	1.4V level	45	50 ±3	55	%
	8.000 ~ 150.000	1.4V level	40	50 ±3	60	%
RISE TIME (T_R)	1.000 ~ 24.999	0.4V ~ 2.4V			10	nS
	25.000 ~ 69.999	0.5V ~ 2.4V			5	nS
	70.000 ~ 150.000	0.5V ~ 2.4V			4	nS
FALL TIME (T_F)	1.000 ~ 24.999	2.4V ~ 0.4V			10	nS
	25.000 ~ 69.999	2.4V ~ 0.5V			5	nS
	70.000 ~ 150.000	2.4V ~ 0.5V			4	nS
OUTPUT VOLTAGE (V_{OL})	1.000 ~ 24.999	$I_{OL} = 20$ mA			0.4	V
	25.000 ~ 150.000	$I_{OL} = 20$ mA			0.5	V
	70.000 ~ 150.000	$I_{OH} = 1$ mA	2.4			V
OUTPUT CURRENT (I_{OL})	1.000 ~ 150.000	$V_{OL} = 0.5$ V			20	mA
	1.000 ~ 150.000	$V_{OH} = 2.4$ V			1.0	mA
OUTPUT LOAD	1.000 ~ 150.000				10	TTL
START-UP TIME (T_s)	1.000 ~ 3.499				20	mS
	3.500 ~ 3.999				35	mS
	4.000 ~ 5.999				30	mS
	6.000 ~ 19.999				20	mS
	20.000 ~ 150.000				15	mS
SUPPLY VOLTAGE	1.000 ~ 150.000	+5.0 ±0.25			—	VDC

* Inclusive of 25°C tolerance, operating temperature range, input voltage change, load change, aging, shock and vibration.

PACKAGE DIMENSIONS (mm)




Figure 1) ECS-100X Series Side and Bottom views




Figure 2) Output Wave Form

PIN CONNECTIONS	
#1	NC
#7	CASE GND
#8	OUTPUT
#14	+5 V DC

Figure 3) Pin Connections

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ECS:

[ECS-100AX-1.2288MHZ](#) [ECS-100AX-110.5](#) [ECS-100AX-1.2288](#) [ECS-100AX-9.216](#) [ECS-100AX-2.0](#) [ECS-100AX-4.9152](#) [ECS-100AX-24.0](#) [ECS-100AX-12.0](#) [ECS-100AX-40.0](#) [ECS-100AX-16.0](#) [ECS-100AX-1.8432](#) [ECS-100AX-27.0](#) [ECS-100AX-25.0](#) [ECS-100AX-30.0](#) [ECS-100AX-18.0](#) [ECS-100AX-48.0](#) [ECS-100AX-9.8304](#) [ECS-100AX-6.0](#) [ECS-100AX-3.579545](#) [ECS-100AX-14.7456](#) [ECS-100AX-16.257](#) [ECS-100AX-2.4576](#) [ECS-100AX-10.0](#) [ECS-100AX-35.0](#) [ECS-100AX-11.0592](#) [ECS-100AX-7.3728](#) [ECS-100AX-5.0](#) [ECS-100AX-6.144](#) [ECS-100AX-010](#) [ECS-100AX-19.6608](#) [ECS-100AX-64.0](#) [ECS-100AX-8.0](#) [ECS-100AX-4.0](#) [ECS-100AX-50.0](#) [ECS-100AX-14.31818](#) [ECS-100AX-66.6666](#) [ECS-100AX-28.322](#) [ECS-100AX-18.432](#) [ECS-100AX-25.175](#) [ECS-100AX-32.0](#) [ECS-100AX-3.6864](#) [ECS-100AX-20.0](#) [ECS-100AX-5.0688](#) [ECS-100AX-020](#)