

# VIP/S/MC/KIT 17-24 - PCB connector



2907268

<https://www.phoenixcontact.com/us/products/2907268>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Pair of screw-clamp plugs to connect to VIP base module labeled 17-24.



## Your advantages

- Screw-clamp terminal wire connection
- Pre-printed channel and shield labeling
- Pluggable for quick and easy connection to base module

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 2907268                        |
| Packing unit                         | 1 pc                           |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | C480                           |
| Product key                          | CK8921                         |
| GTIN                                 | 4055626257013                  |
| Weight per piece (including packing) | 1.05 g                         |
| Weight per piece (excluding packing) | 1 g                            |
| Customs tariff number                | 85366990                       |
| Country of origin                    | US                             |

# VIP/S/MC/KIT 17-24 - PCB connector



2907268

<https://www.phoenixcontact.com/us/products/2907268>

## Technical data

### Product properties

|                |                     |
|----------------|---------------------|
| Product type   | PCB connector       |
| Product family | VIP I/O-Marshalling |

### Electrical properties

|                          |                                              |
|--------------------------|----------------------------------------------|
| Max. permissible current | 8 A                                          |
| Nominal voltage $U_N$    | 300 V (maximum continuous operating voltage) |

### Connection data

#### Controller level

|                                  |                                              |
|----------------------------------|----------------------------------------------|
| Connection method                | Screw connection                             |
| Stripping length                 | 7 mm                                         |
| Number of positions              | 9                                            |
| Conductor cross section rigid    | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> |
| Conductor cross section flexible | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> |
| Conductor cross section AWG      | 28 ... 16                                    |
| Tightening torque                | 0.22 Nm ... 0.25 Nm                          |

### Dimensions

#### Item dimensions

|        |          |
|--------|----------|
| Width  | 44.68 mm |
| Height | 11.1 mm  |

### Mounting

|             |    |
|-------------|----|
| Thread type | () |
|-------------|----|

### Environmental and real-life conditions

#### Ambient conditions

|                                         |                  |
|-----------------------------------------|------------------|
| Ambient temperature (operation)         | -40 °C ... 70 °C |
| Ambient temperature (storage/transport) | -40 °C ... 70 °C |

# VIP/S/MC/KIT 17-24 - PCB connector



2907268

<https://www.phoenixcontact.com/us/products/2907268>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27371392 |
| ECLASS-12.0 | 27371392 |
| ECLASS-13.0 | 27371392 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002498 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121100 |
|-------------|----------|

# VIP/S/MC/KIT 17-24 - PCB connector



2907268

<https://www.phoenixcontact.com/us/products/2907268>

## Environmental product compliance

### EU RoHS

|                                         |                    |
|-----------------------------------------|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|-----------------------------------------|--------------------|

### China RoHS

|                                        |                                                                                                                                                                                                                                   |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Environment friendly use period (EFUP) | EFUP-50                                                                                                                                                                                                                           |
|                                        | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)