


Product information

ASBV 4/LED 5-256/... M - ASBV 4/LED 5-256/5 M

Industrial Connecting Solutions:I/O Modules:Passive distributors:M12 Passive Distributors:fixed control cable:with LED:2 signals/socket (4+PE):ASBV 4/LED 5-256/... M

http://www.e-catalog.beldensolutions.com/link/57078-24228-255441-199791-200292-204934-204940-204949-205180/en/ASBV_04_LED_5_256_05/uistate

| Name | |
|--|--|
| ASBV 4/LED 5-256/... M | |
|  | |
| Actuator/sensor distribution box, 4-port version, with LED operation and function indicators, combined FIXCON-/M12 socket, 5-pole, 2 signals per socket, earth connection, fixed connection cable, PUR jacket, halogen-free, black, 5 meter. | |
| Delivery informations | |
| Availability | available |
| Product description | |
| Type | ASBV 4/LED 5-256/5 M |
| Order No. | 11147 |
| Description | Actuator/sensor distribution box, 4-port version, with LED operation and function indicators, combined FIXCON-/M12 socket, 5-pole, 2 signals per socket, earth connection, fixed connection cable, PUR jacket, halogen-free, black, 5 meter. |
| Number of contacts | 5 (M12) |
| Version | 4 ports |
| Color of housing | orange |
| Product characteristics | Vibration resistance, Oil resistance, Drag chains suitable |
| Classification | |
| Belden brand | Lumberg-Automation |
| Mechanical data | |
| Thread | M12 |
| LED display present | ✓ |
| Environmental conditions | |
| Environmental temperature | -15 °C ... 80 °C |
| Degree of protection (IP), mounted | IP67 |
| Pollution degree | 3 |
| Materials | |
| Housing material / Molded body | TPU, self-extinguishing |
| Contact bearer material | PA-GF, self-extinguishing |
| Contact material | CuZn (M12) |
| Contact material - Surface refinement | pre-nickel and 0.8 microns gold-plated |
| Knurled screw / nut material | CuZn, nickel-plated |
| Sealing material | FKM |
| Electrical data | |
| Contact resistance | ≤ 5 mΩ |
| Rated current In | 4 A per socket / 12 A max. at 40°C |
| Nominal voltage | 10 - 30 V DC |
| Rated voltage | 32 V |
| Insulation resistance | > 1 GΩ |
| Approvals | |
| Approvals | cURus |
| Cable | |
| Cable length | 5 m |
| Cable number | 256 |
| Cable description | Cable for actuator/sensor distribution boxes |
| Color of jacket | black |
| Material of outer jacket | PUR |
| Outer diameter of the cable | 9.3 mm |


Industrial Connecting Solutions:I/O Modules:Passive distributors:M12 Passive Distributors:fixed control cable:with LED:2 signals/socket (4+PE):ASBV 4/LED 5-256/... M

http://www.e-catalog.beldensolutions.com/link/57078-24228-255441-199791-200292-204934-204940-204949-205180/en/ASBV_04_LED_5_256_05/ui/state

| | |
|---------------------------------------|--|
| Number of conductors | 11 |
| Cable design | 8 x 0.5 mm ² + 3 x 1.0 mm ² |
| Flame resistant according to standard | IEC 60332-2, CSA FT-2 |
| Scope of delivery and accessories | |
| Scope of delivery | ZVK: 2 dust covers for unused sockets ZBS: 10 attachable labels |

Picture

Drawing



Belden Deutschland GmbH

Im Gewerbepark 2
58579 Schalksmühle
Germany
Phone: +49 7127/14-1806
E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.