



Switches > Snap Action Switches



Configuration (Pole-Throw): **Single Pole - Double Throw**

Actuator Style: **Pin Plunger**

Contact Current Rating: **26 A**

Operating Voltage: **250 VDC**

Features

Product Type Features

Actuator Style	Pin Plunger
Switch Connection Type	Quick Connect Terminal
Switch Style	Miniature

Configuration Features

Operating Position	14.7 mm[.578 in]
Configuration (Pole-Throw)	Single Pole - Double Throw

Electrical Characteristics

Contact Current Rating	26 A
Operating Voltage	250 VDC

Body Features

Movement Differential	.4 mm[.015 in]
Releasing Force	55 g[1.94 oz]
Product Orientation	Vertical

Dimensions

Pre Travel	1.9 mm[.074 in]
------------	-----------------



Operation/Application

Operating Force	350 g
-----------------	-------

Other

Over Travel	1 mm[.039 in]
-------------	---------------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE’s information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) ‘Guidance on requirements for substances in articles’(Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of ‘complex object’, the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA “Guidance on requirements for substances in articles” (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts



TE Part # 2435262-2

HCP 26A, Hvt Force, 0.250 Term. No LVR

Customers Also Bought

TE Part #770076-1

04P .093 COMM P&S RECPT HSG

TE Part #3-1437664-8

NC6-P108-06=NC6 ASSEMBLY

TE Part #770077-1

04P .093 COMM P&S PLUG HSG

TE Part #2071540-1

TMR120-1H4-B012D10,03000

TE Part #770089-1

06P .093 COMM P&S PLUG HSG

TE Part #41291

250 FASTON,TAB,BR

TE Part #1-2435262-1

HCP26A, Hvt Force,0.187 Term. SHT Roller

TE Part #2435262-2

HCP 26A, Hvt Force, 0.250 Term. No LVR

TE Part #1-2435262-2

HCP26A, Hvt Force,0.250 Term. SHT Roller

Documents

Product Drawings

HCP 26A, Hvt Force, 0.187 Term. No LVR

English

CAD Files

Customer View Model

ENG_CVM_CVM_2435262-1_A.3d_stp.zip

English

Customer View Model



[ENG_CVM_CVM_2435262-1_A.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2435262-1_A.3d_igs.zip](#)

English

3D PDF

3D

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[ALCOSWITCH_HCP_SERIES](#)

English