

Coaxial PCB Connector 85_BNC-75-0-1/133_N

Description

Right angle PCB jack

Interface Standards

Interface compatible with IEC 61169-8



Technical Data

Electrical Data

| | |
|--------------------------|-------------|
| Impedance | 75 Ω |
| Interface frequency max. | 1 GHz |

Mechanical Data

| | |
|---------------------|---------------|
| Board mounting type | through holes |
| Weight | 0.0152 kg |

Environmental Data

| | |
|-----------------------|------------------|
| Operating temperature | -65 °C to 165 °C |
| 2011/65/EU (RoHS) | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|--------------------------|-----------------------------------|
| Centre contact | Copper Beryllium / Brass | Gold Plating (Nickel underplated) |
| Outer contact | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PFA / PTFE | |

Related Documents

| | |
|-------------------|--------------|
| Outline drawing | DOU-00012866 |
| Catalogue drawing | DCA-00012868 |
| Mounting hole | DOU-00012084 |

Ordering Information

| | |
|----------------------|----------------------|
| Bulk 100 pcs package | 85_BNC-75-0-1/133_NH |
| Single package | 85_BNC-75-0-1/133_NE |

Remarks

PCB connector with stand-offs

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER:

[85_BNC-75-0-1/133_NH](#) [85_BNC-75-0-1/133_NE](#)