




Part Number : [309681127](#)
Product Description : 2.54mm Pitch, 0.64mm Width H-DAC 64 High Density Automotive Crimp Housing, Dual Row, 12 Circuits, Polarization Option #1, Gray
Series Number : 30968
Status : Active
Product Category : Connector Housings



Documents & Resources

Drawings
[Drawing 309681127_sd.pdf](#)
[Packaging Design Drawing PK-30907-760-001.pdf](#)

3D Models and Design Files
[3D Model 309681127_stp.zip](#)

Specifications
[Application Specification AS-30700-000-001.pdf](#)
[Product Specification PS-30968-0001-001.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Compliant
China RoHS	
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements
- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents
- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Connector Housings
Series	30968
Description	2.54mm Pitch, 0.64mm Width H-DAC 64 High Density Automotive Crimp Housing, Dual Row, 12 Circuits, Polarization Option #1, Gray
Application	Automotive, Power, Wire-to-Wire
Comments	Polarization Option #1
Product Name	H-DAC 64
UPC	822348870400

Physical

Circuits (maximum)	12
Color - Resin	Gray
Gender	Plug
Glow-Wire Capable	No
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Resin	Modified Polystyrene
Net Weight	5.706/g
Number of Rows	2
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	2.54mm
Polarized to Mating Part	Yes
Stackable	No
Temperature Range - Operating	-40° to +100°C

Solder Process Data

Lead-Free Process Capability	N/A
------------------------------	-----

Mates With / Use With

Mates with Part(s)

Description	Part Number
H-DAC 64 High Density Automotive Connectors	<u>30700</u>

Use with Part(s)

Description	Part Number
Use With	Contact Molex for Terminal information.