



MQS

TE Internal #: 1-1241370-3
Housing for Female Terminals, Wire-to-Board / Wire-to-Device / Wire-to-Wire, 6 Position, 2.54 mm [.1 in] Centerline, Black, Wire & Cable, Signal
[View on TE.com >](#)

Connectors > Automotive Connectors > Automotive Housings > MQS, CONNECTOR HOUSING



Connector System: Wire-to-Board, Wire-to-Device, Wire-to-Wire
Number of Positions: 6
Connector & Housing Type: Housing for Female Terminals
Centerline (Pitch): 2.54 mm [.1 in]
Sealable: No

[All MQS, CONNECTOR HOUSING \(360\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Board, Wire-to-Device, Wire-to-Wire
Connector & Housing Type	Housing for Female Terminals
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	On the Terminal

Configuration Features

Number of Positions	6
Number of Rows	1

Electrical Characteristics

Operating Voltage	50 VDC
Nominal Voltage Architecture	50 V

Body Features

Cable Exit Angle	180°
Primary Product Color	Black



Connector & Keying Code	A
-------------------------	---

Contact Features

Contact Size	.63mm
Contact Type	Receptacle
Mating Tab Width	.63 mm[.025 in]
Contact Current Rating (Max)	7.5 A

Mechanical Attachment

Terminal Position Assurance	Yes
Strain Relief	Without
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PBT GF
Centerline (Pitch)	2.54 mm[.1 in]

Dimensions

Connector Height	16.6 mm[.654 in]
Product Width	5.4 mm[.213 in]
Product Length	18.2 mm[.717 in]

Usage Conditions

Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F]
Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]

Operation/Application

Circuit Application	Signal
---------------------	--------

Packaging Features

Packaging Method	Carton
------------------	--------

Other

Serviceable	No
Connector Position Assurance Capable	No



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts


TE Part # 2-969682-1
6pos MQS .63 header 90deg SMD

TE Part # CAT-M8793-T273
MQS, RECEPTACLE AND TAB


TE Part # 2317023-1
6pos MQS .63 header 90deg SMD

Customers Also Bought







TE Part #2-967624-1
JUN-POW-TIM GEH 18P




TE Part #1703874-1
MQS, CONNECTOR HOUSING




TE Part #1355922-1
GET GEH. 6P




TE Part #1379671-5
40W PLUG HSG ASSY NATURAL




TE Part #1745078-2
AMP MCP 2.8K - REC. ASSY



TE Part #284818-2
1 WAYS CONNECTOR F.GLOW PLUG
- RED VERS.



TE Part #K1162721
Relay 29-311-02-981



TE Part #1544266-1
FUSE BOX ASSY LEADFRAME BFH12

TE Part #2340311-1
2POS,MCON 1.2,TAB HSG,UNSLD,
COD A

Documents

Product Drawings
6POS MQS REC COD A

German

CAD Files
Customer View Model
ENG_CVM_CVM_1-1241370-3_D.2d_dxf.zip

English

3D PDF

3D

Customer View Model
ENG_CVM_CVM_1-1241370-3_D.3d_igs.zip

English

Customer View Model
ENG_CVM_CVM_1-1241370-3_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications



Application Specification

English