



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Header**

Connector & Housing Type: **Receptacle**

Connector System: **Wire-to-Board**

Number of Positions: **4**

Centerline (Pitch): **6.35 mm [.25 in]**

Features

Product Type Features

Rectangular Power Connector Type	Header
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	4
PCB Mount Orientation	Vertical
Number of Power Positions	4
Number of Rows	1

Electrical Characteristics

Operating Voltage	600 VAC
-------------------	---------

Contact Features

Multiple Contact Types	Without
------------------------	---------



Contact Layout	Inline
Contact Mating Area Plating Material	Tin
Contact Current Rating (Max)	12 A
Contact Retention Within Housing	Without
Contact Type	Socket
PCB Contact Termination Area Plating Material	Pre-Tin
Contact Mating Area Plating Material Thickness	3.81 – 5.08 µm[150 – 200 µin]

Termination Features

Termination Post & Tail Length	3.94 mm[.155 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Strain Relief	Without
Mating Alignment Type	Polarization
Mating Retention	With
Mating Alignment	With
PCB Mount Alignment	Without
Panel Mount Feature	Without
PCB Mount Retention	Without
Mating Retention Type	Positive Lock
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	6.35 mm[.25 in]
Housing Color	Natural
Housing Material	Nylon

Dimensions

PCB Thickness (Recommended)	.06 mm[1.57 in]
-----------------------------	-----------------

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

UL Rating	Recognized
-----------	------------



Compatible With Agency/Standards Products	UL, VDE
Compatible With Approved Standards Products	UL E28476
UL Flammability Rating	UL 94V-2
Glow Wire Rating	GWT 750°C (Without Flame)

Packaging Features

Packaging Quantity	100
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



 TE Part # 1-480703-9 04P UMNL CAP HSG BLK	 TE Part # 643415-1 04P UMNL HDR ASSY POL	 TE Part # 350759-4 02P UMNL HDR ASSY PC V2 NATL	 TE Part # 350760-4 03P UMNL HDR ASSY PC
 TE Part # 1-480703-0 04P UMNL CAP HSG NATL	 TE Part # 2029361-1 05P UMNL SOC HDR V2 NATL NDH	 TE Part # 1586845-1 04P UMNL CAP HSG NATL, GW	 TE Part # 1586086-1 04P UMNL PIN HDR ASSY W/O DRNS
 TE Part # 350761-4 04P UMNL HDR ASSY PC	 TE Part # 1586953-1 02P UMNL PIN HDR ASSY NATL, GW	 TE Part # 926305-6 UNML4WAY CAP	 TE Part # 1-480703-1 04P UMNL CAP HSG BRN
 TE Part # 350584-1 04P UMNL PIN HDR ASSY V2 NATL	 TE Part # 1-350780-9 04P UMNL V0 CAP HSG BLACK	 TE Part # 1-350948-0 04P UMNL HDR ASSY R/A V2 NATL	 TE Part # 1-480703-2 04P UMNL CAP HSG RED
 TE Part # 794707-1 04P UMNL CAP HSG, BLACK	 TE Part # 1586968-1 05P UMNL PIN HDR ASSY V2, GW	 TE Part # 1586958-1 03P UMNL PIN HDR ASSY NATL, GW	 TE Part # 350988-4 04P UMNL HDR ASSY LNG/TL

Also in the Series | Universal MATE-N-LOK



Circular Power Connectors(2)



Connector Caps & Covers(34)



Connector Contacts(209)



Connector Hardware(12)



Connector Seals & Cavity Plugs(27)



Connector Strain Relief(7)



Insertion & Extraction Tools(4)



Rectangular Connector Housings(1)



Rectangular Power Connectors(670)



Standard Circular Connectors(1)

Customers Also Bought




TE Part #5787082-7
68 50SR R/A RCPT ASSY,RDSN L/F



TE Part #1586953-1
02P UMNL PIN HDR ASSY NATL, GW




TE Part #1571983-8
GDH06S04=DIP SWITCH



TE Part #280611-1
6P MOD 1 SHROUDED HEADER, ST, TIN PLTD




TE Part #5-1625885-5
1W SM M/OX 5% 2R2



TE Part #2176331-7
CRGP 2512 33R 1%



TE Part #1011-269-0605
BKSHL, 6P, BLK, REC, ST, SR, NW8.5 /10/13



TE Part #1586963-1
04P UMNL PIN HDR ASSY, GW /10/13



Documents

Product Drawings

04P UMNL HDR ASSY, GW

English

CAD Files

Customer View Model

ENG_CVM_1586872-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_1586872-1_A.3d_stp.zip

English

Customer View Model

ENG_CVM_1586872-1_A.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Agency Approvals

VDE Certificate

English

VDE Certificate

English