



PCB图仅供参考

Note:

1. Material:
  - 1.1 Housing: High temperature thermoplastic with g.f.Ul94v-0
  - 1.2 Contact: copper alloy,t=0.15mm
  - 1.3 Shell: copper alloy,t=0.30mm
2. Specification:
  - 2.1 Current rating:1.5PIN 1.8A Max/2.3,4PIN 1A Max.
  - 2.2 Dielectric withstanding voltage: 100 V(ac) for 1 min.
  - 2.3 Contact resistance: 30 mΩ Max.
  - 2.4 Insulation resistance: 100 MΩ Min.
  - 2.5 Total mating force: 3.57 Kgf Max.
  - 2.6 Total unmating force: 1.0 Kgf Min.
  - 2.7 Temperature range: -30°C~80°C

		深圳市万骏达电子有限公司 <a href="http://www.wanjunda.com">http://www.wanjunda.com</a>		图号 (DWG NO)		单位 (UNIT):	MM
品名 (ITEM NO)	MICRO 5#牛角平口	版本 (REV)		比例 (SCALE):	1:1	公差 (TOLERANCE UNSPECIFIED)	X X ±0.30 X XX ±0.20 X XXX ±0.10 X X* ±0.05 X X* ±0.02
料号 (PART NO)	MICRO-5F-ZB-NJ-4.85	日期 (DATE)		设计 (DESIGN)		审核 (CHECKED)	
型号 (MODEL NO)		核准 (APPROVED)					