Product data sheet Characteristics

XZCPV0566L2

pre-wired connectors XZ - straight female - M8 - 3 pins - cable PVC 2m

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Commercial Status	Commercialised
Accessory / separate part category	Cabling accessories
Accessory / separate part type	Pre-wired connectors
Series name	General purpose
Electrical connection	Straight female connector M8, 3 pins
Collar material	Metal
Status LED	Without
Cable length	6.56 ft (2 m)

Complementary

Cable connector fixing	Screw-on
Cable outer diameter	0.18 in (4.6 mm)
Cable composition	3 x 0.25 mm²
Wire insulation material	PVC
[Ue] rated operational voltage	75 V DC 60 V AC
[In] rated current	3 A
Contact resistance	<= 5000 μOhm
Insulating resistance	>= 1 GΩ
Product weight	0.19 lb(US) (0.084 kg)

Environment

IP degree of protection	IP67
Ambient air temperature for operation	-13176 °F (-2580 °C) (static)
Ambient air temperature for storage	-13176 °F (-2580 °C)

Ordering and shipping details

stocked in distribution facility
- 5

Contractual warranty

Period	18 months

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XZCPV0566L2