

## RC-06S1NS2Z500 - 1594229

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Cable connector, with Pg9 connection thread, angled, shielded: no, Screw locking, M23, No. of pos.: 6, type of contact: Socket, Screw connection, cable diameter range: 6 mm ... 10 mm



## **Key Commercial Data**

| Packing unit | 8 pc            |
|--------------|-----------------|
| GTIN         | 4 046356 200318 |
| GTIN         | 4046356200318   |

## Technical data

#### Data of the insulating body

| Coding   | N                |
|--|------------------|
| Insertion/withdrawal cycles mechanical         | 50               |
| Contact connection method                      | Screw connection |
| Type of contacts                               | Socket           |
| Application                                    | Signal           |
| Number of positions                            | 6                |
| Contact diameter of power contacts             | 2 mm             |
| Litz wire cross section of power contacts min. | 0.08 mm²         |
| Litz wire cross section of power contacts max. | 1 mm²            |
| Nominal current per power contact at 25°C      | 20 A             |
| Nominal voltage, power contact                 | 150 V            |
| Rated surge voltage                            | 2.5 kV           |
| Overvoltage category                           | II               |
| Degree of pollution                            | 3                |
| Overvoltage category                           | II               |
| Degree of pollution                            | 3                |

## Housing data

| Note                                   | Order information: Order contact inserts and cable clamping separately |
|--|--|
| Housing material                       | Metal  |
| Type of locking                        | Screw locking  |
| Degree of protection (when plugged in) | IP65   |
|  | IP67   |



# RC-06S1NS2Z500 - 1594229

## Technical data

## Housing data

|  | Thread type | M23 |
|--|-------------|-----|
|--|-------------|-----|

#### Cable seal data

| Cable diameter | 6 mm 10 mm |
|----------------|------------|
|                |            |

## **Environmental Product Compliance**


| REACh SVHC | Lead 7439-92-1  |
|------------|---|
| China RoHS | Environmentally Friendly Use Period = 50  |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Drawings

### Schematic diagram



### Dimensional drawing



## **Approvals**

Approvals

Approvals

EAC

Ex Approvals

## Approval details

EAC [FI]



Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1594229