

AMP | AMP CPC

TE Internal #: 206037-4


Housing, 600 VDC, Wire-to-Wire, 16 Position, Wire & Cable, Plug, Socket, Power & Signal, Black, All Plastic, AMP CPC, Circular Power

Connectors

View on TE.com >



Connectors > Power Connectors > Circular Power > Circular Power Connectors



Connector Product Type: Housing

Operating Voltage: 600 VDC

Connector System: Wire-to-Wire

Number of Positions: 16

Sealable: No

Features

Product Type Features

Connector Product Type	Housing
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Connector & Housing Type	Plug
Circular Connector Shell Type	All Plastic

Configuration Features

Reverse Numbering	Without
Number of Positions	16
Number of Power Positions	0
Number of Signal Positions	16

Electrical Characteristics

Operating Voltage	600 VAC	

Contact Features

Reverse Gender	No
Contact Type	Socket
Contact Protection	With

Mechanical Attachment



Mating Alignment Type	Keyed
Mating Alignment	With
Mating Retention Type	Threaded Coupling
Thread Size	15/16-20 UNEF – 2A
Polarization Code	A
Connector Mounting Type	Cable Mount (Free-Hanging)
Mating Retention	With
Panel Mount Feature	Without
Housing Features	
Body Orientation	Straight
Housing Color	Black
	The arms and action
Housing Material	Thermoplastic
Housing Material Circular Connector Shell Size	17
Circular Connector Shell Size	
Circular Connector Shell Size Usage Conditions	17
Circular Connector Shell Size Usage Conditions Operating Temperature Range	17 -55 – 105 °C[-67 – 221 °F]
Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance	17 -55 – 105 °C[-67 – 221 °F]
Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application	17 -55 – 105 °C[-67 – 221 °F] None
Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application	17 -55 – 105 °C[-67 – 221 °F] None Power & Signal
Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application Shielded	17 -55 – 105 °C[-67 – 221 °F] None Power & Signal
Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application Shielded Industry Standards	17 -55 – 105 °C[-67 – 221 °F] None Power & Signal No
Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application Shielded Industry Standards UL Flammability Rating	17 -55 – 105 °C[-67 – 221 °F] None Power & Signal No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241)



Candidate List Declared Against: JUNE 2024 (241)

Does not contain REACH SVHC

Halogen Content

BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 206552-1 CPC RECPT ASSEMBLY SIZE 17-16



TE Part # 206036-8
RECEPT,SZ 17-16 CPC,W/INSERTS



TE Part # 206036-4
CPC RECPT SEALED SIZE 17-16



TE Part # 206207-1 17-3 RECEPT. FREE-HANGING



TE Part # 206036-3

RECEPT,SZ 17-16,CPC



TE Part # 206036-1 RECEPT,SZ 17-16 CPC



TE Part # 206036-5 CPC RECPT ASSEMBLY SIZE 17-16



TE Part # 206036-2 CPC RECEPTACLE SIZE 17-3



TE Part # 1-796404-1 CPC PSTD RCPT,17-16,R/A LF



TE Part # 213581-1 CPC STND SEX 17-3 THRD INSERTS





Also in the Series | AMP CPC



Circular Power Connectors(425)



Connector Backshells(1)



Connector Caps & Covers(16)



Connector Contacts(6)



Connector Hardware(12)



Connector Seals & Cavity Plugs(35)



Connector Strain Relief(60)




Insertion & Extraction Tools(1)



Sealing Sleeves(2)


Customers Also Bought



TE Part #213933-1 CPC,STRAIN RELIEF,SIZE 17




TE Part #206036-1 RECEPT,SZ 17-16 CPC



TE Part #1-206062-7 CABLE CLAMP KIT, BULK PKG





TE Part #3-640599-7 07P MTA156 CONN ASSY 18AWG ORA



TE Part #66101-4
III+ SKT,18-16,30AU/FL,LP



TE Part #5748678-1 2 PC PLST CBL CLMP KIT







Documents

Product Drawings

CPC PLUG ASSEMBLY SZ 17-16

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_206037-4_S.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_206037-4_S.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_206037-4_S.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English