

## Coaxial Cable Connector 11\_SMA-50-3-42/-33\_N

### Description

Straight cable plug

Interface standards

SUHNER-SMA-26.5GHz



### Technical Data

#### Electrical Data

|                          |             |
|--------------------------|-------------|
| Impedance                | 50 $\Omega$ |
| Interface frequency max. | 26.5 GHz    |

#### Mechanical Data

|                |           |
|----------------|-----------|
| Centre contact | soldered  |
| Outer contact  | soldered  |
| Weight         | 0.0033 kg |

#### Environmental Data

|                       |                  |
|-----------------------|------------------|
| Operating temperature | -65 °C to 165 °C |
| 2011/65/EU, RoHS      | compliant        |

#### Material Data

| Piece Parts    | Material              | Surface Plating       |
|----------------|-----------------------|-----------------------|
| Centre contact |                       |                       |
| Outer contact  | Brass                 | SUCOPLATE (R) Plating |
| Body           | Brass                 | SUCOPLATE (R) Plating |
| Coupling nut   | Brass                 | SUCOPLATE (R) Plating |
| Gasket         | VMQ (Silicone rubber) |                       |

### Related Documents

|                      |                |
|----------------------|----------------|
| Outline drawing      | DOU-00006525   |
| Catalogue drawing    | DOU-00006518   |
| Assembly instruction | DOC-0000179294 |

### Ordering Information

|                      |                       |
|----------------------|-----------------------|
| Bulk 100 pcs package | 11_SMA-50-3-42/-33_NH |
| Single package       | 11_SMA-50-3-42/-33_NE |

### Additional Information

|                 |               |
|-----------------|---------------|
| Suitable cables | EZ_141_TP_M17 |
|-----------------|---------------|

### Remarks

EI. Optimized for cable RG 58 C/U

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER:

[11\\_SMA-50-3-42/-33\\_NE](#) [11\\_SMA-50-3-42/-33\\_NH](#)