



Ordering Information:

A5082H-XP - ***
1 2

1.Part NO.

2.Material:

(blank): Nylon 66,UL94V-2 (Natural)

V0: Nylon 66,UL94V-0 (White)

GWT: Nylon 66,UL94V-0(Beige),

IEC 60335-1,5th Edition

Glow Wire Capable.

SPECIFICATIONS:

Current Rating: 7A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 10mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 1500V AC/minute

Material: Nylon 66,UL94V-2

Ordering Information & Dimensions

Part NO.	Dimensions(mm)	
	A	B
A5082H-2P	5.08	10.08
A5082H-3P	10.16	15.16
A5082H-4P	15.24	20.24
A5082H-5P	20.32	25.32
A5082H-6P	25.40	30.40
A5082H-7P	30.48	35.48
A5082H-8P	35.56	40.56
A5082H-9P	40.64	45.64

CJTconn CHANGJIANG CONNECTORS CO.,LTD.

Unit: mm, Scale: 3:1, Sheet: 1 of 1

DRWN: Dengchun Yi, CHK'D: Dlankul Wan, APPR: Jack Yin

General Tolerances: x.xx±0.25, x.xxx±0.20, x.xxxx±0.15, ANGLES ±1°

TITLE: 5.08mm PITCH HOUSING

DRAWING NO.: A5082H-XP, REV: A1

REV	DESCRIPTION	DATE
A1	CHANGE THE DRAWING	2020.05.13
A0	NEW RELEASE	2009.05.10