

3240855

https://www.phoenixcontact.com/us/products/3240855

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Protective hose, material: PVC, filament: PVC sheathed spring steel, UV-resistant: no, flexible, degree of protection: IP68, color: gray, inner diameter: 38 mm, Total length: 10 m

Commercial data

| Item number | 3240855 |
|--------------------------------------|---------------------|
| Packing unit | 1 m |
| Minimum order quantity | 1 m |
| Sales key | BF68 |
| Product key | BF7DSA |
| Catalog page | Page 592 (C-3-2019) |
| GTIN | 4046356736817 |
| Weight per piece (including packing) | 999.9 g |
| Weight per piece (excluding packing) | 999.9 g |
| Customs tariff number | 39173200 |
| Country of origin | DE |



3240855

https://www.phoenixcontact.com/us/products/3240855

Technical data

Notes

| Notes on operation | Protective hose length is measured stretched out; length tolerance ±5% |
|--------------------|--|
| oduct properties | |

Prod

| Product type | Corrugated pipe |
|----------------------|-----------------|
| Tensile strength GRP | 100 N |

Dimensions

External dimensions

| Outside diameter | 45 mm | |
|---------------------|-------|--|
| Internal dimensions | | |
| Internal diameter | 38 mm | |

Material specifications

| Material | PVC |
|---------------|--------------------------------|
| Material Coil | PVC |
| Components | Free from silicone and cadmium |

Cable/line

| Bending radius, dynamic | 90 mm |
|-------------------------|-------|
| Bending radius, static | 36 mm |
| Tensile strength | 100 N |
| Halogen-free | no |

Environmental and real-life conditions

Ambient conditions

| Degree of protection | IP68 |
|---------------------------------|--------------|
| Ambient temperature (operation) | -25 °C 90 °C |
| Resistance to UV radiation | no |
| Short-term temperature | 100 °C |



3240855

https://www.phoenixcontact.com/us/products/3240855

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/3240855



VDE Zeichengenehmigung



3240855

https://www.phoenixcontact.com/us/products/3240855

Classifications

UNSPSC 21.0

ECLASS

| | ECLASS-11.0 | 27430304 |
|--------|-------------|----------|
| | ECLASS-13.0 | 27430304 |
| | ECLASS-12.0 | 27430304 |
| ETIM | | |
| | ETIM 9.0 | EC001177 |
| UNSPSC | | |

40141700



3240855

https://www.phoenixcontact.com/us/products/3240855

Environmental product compliance

| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--|
| China RoHS | |
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |
| EU REACH SVHC | |
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |



3240855

https://www.phoenixcontact.com/us/products/3240855

Accessories

WP-SC HF 45 - Cable protection end sleeve

3241022

https://www.phoenixcontact.com/us/products/3241022



Cable protection end sleeve, material: PP, color: gray, flammability rating in acc. with UL 94: HB, inner diameter: 36 mm

WP-G PP HF PG36 - Screw connection

3240994

https://www.phoenixcontact.com/us/products/3240994



Cable gland made from PP with Pg thread, IP65 protection



3240855

https://www.phoenixcontact.com/us/products/3240855

WP-G PP HF M40 - Screw connection

3241001

https://www.phoenixcontact.com/us/products/3241001



Cable gland made from PP with metric thread, IP65 protection

WP-GT PP HF PG36 - Screw connection

3241008

https://www.phoenixcontact.com/us/products/3241008



Cable gland made from PP with Pg thread, rotatable, IP54 protection



3240855

https://www.phoenixcontact.com/us/products/3240855

WP-BASE HF 45 - Hose clamp

3240973

https://www.phoenixcontact.com/us/products/3240973



Hose clamp, material: Steel, galvanized, color: black/silver

WP-BASE A PG36 - Protective hose fixing bracket

3241082

https://www.phoenixcontact.com/us/products/3241082



Fixing bracket for protective sleeves, fixed with two screws

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com