

F

E


D

C

B

A

SAP P/N #	ENGINEERING P/N	FINISHED LENGTH
1300640468	CC4032K24M100	10.0M (32.8')
1300640469	CC4032K24M150	15.0M (49.2')
1300642052	CC4032K24M030	3.0M (9.8')



- NOTES:
1. MATERIAL: AS NOTED
 2. FINISH: AS NOTED
 3. ELECTRICAL:
VOLTAGE: 500V PER IEC60664
600V PER UL2238
CURRENT: 32A
 4. TEMP RATING: -25° TO +90°C
 5. PROTECTION: IP67 (WHEN MATED)
 6. COUPLING THREAD: 7/8-16UN
 7. UL2237 STATUS: PENDING
 7. ALL DIMS ARE FOR REFERENCE UNLESS NOTED OTHERWISE

10	1	WRAP LABEL	VINYL	YELLOW
9	2	WARNING LABEL	VINYL	BLACK/ORANGE/YELLOW
8	1	FEMALE COUPLING NUT	ALUMINUM ALLOY	CLEAR ANODIZED
7	4	SOCKET CONTACT	COPPER ALLOY	GOLD PLATED
6	1	4P FEMALE INSERT	PVC	BLACK
5	A/R	OVERMOLD COMPOUND	PVC	GRAY
4	1	MALE COUPLING NUT	ALUMINUM ALLOY	CLEAR ANODIZED
3	1	4P MALE INSERT	PVC	BLACK
2	4	90D PIN CONTACT	COPPER ALLOY	GOLD PLATED
1	-	#10-4 AWG VFD FLEX-RATED CABLE	TPE JACKET	BLACK
ITEM	QTY	DESCRIPTION	MATERIAL	FINISH

CHANGE TO SD EC NO: IPG2018-0452 DRWN: MZIELINS 2018/04/04 CHKD: RSTONE 2018/04/05 APPR: BWOODMAN2016/01/07	DESCRIPTION	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)			DIMENSION STYLE		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION		
		 =0  =0		mm	INCH	DRAWN BY	DATE	TITLE QC M/FE 90D/STR 4P #10-4 AWG VFD FLX-RATED TPE BLK CABLE				
			4 PLACES	±---	±---	MZIELINS	2015/12/09					
			3 PLACES	±---	±.005	CHECKED BY	DATE	MOLEX INCORPORATED				
			2 PLACES	±0.13	±.010	BARDEN	2015/01/06					
			1 PLACE	±0.25	±.020	APPROVED BY	DATE	DOCUMENT NO. SD-130064-023				
		ANGULAR ±---°			BWOODMAN	2016/01/07	SHEET NO. 1 OF 1					
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			MATERIAL NO. SEE CHART							THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION
					SIZE							
				B								

PART NUMBER MATRIX

CC4032K24M010

LENGTH

M005 = .5 METER

M010 = 1 METER

M100 = 10 METER

CABLE LENGTH TOLERANCES

>.3M [1FT]: +19mm-0 [+.75in-0]

.3 - .9M [1 - 3FT]: +44.5mm-0 [+1.75in-0]

.9 - 1.8M [3 - 6FT]: +55.6mm-0 [+2.19in-0]




1.8 - 3.7M [6 - 12FT]: +88.9mm-0 [+3.50in-0]

3.7 - 7.3M [12 - 24FT]: +165.1mm-0 [+6.50in-0]

7.3-14.6M [24 - 48FT]: +317.5mm-0 [+12.50in-0]

14.6 - 30.5M [48-100FT]: +622.3mm-0 [+24.50in-0]

OVER 30M [100FT] +2% OF FINISHED LENGTH



F

E

D

C

B

A

10

9

8

7

6

5

4

3

2

1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Molex:

1300640489