



[Sitemap](#)
[Masthead](#)


 english
 

[HOME](#)
[PRODUCTS](#)
[CATALOGUE](#)
[COMPANY](#)
[LATEST NEWS](#)
[SERVICE](#)
[CONTACT](#)
[0 ARTICLES](#)

You are here: [Products](#) » [Connectors f.con](#) » [PCB connectors](#) » [Jumpers](#) » [SL 8 ...](#) » **SL 8**




▶ Heatsinks f.cool

▶ Cases f.case

▼ **Connectors f.con**

▶ Sockets

▼ PCB connectors

- Male headers
- Female headers
- Direct female connector
- **Jumpers**

▶ IDC-connectors

▶ D-Sub connectors

■ Brackets for PC

▶ Optoelectronics

Jumpers

SL 8 ...

SL 8 20 Z

Low profile

[add to request](#)




Features

Technical Drawing

Accessories / related products

no. of contacts	20
contact material	CuSn alloy
surface contact / contact sleeve	Ni+≥0.2µm Au
	Ni+4...6µm Sn
surface of contact	tin-plated
volume resistivity	≤5 mΩ
nominal current	3 A
nominal voltage	250 V AC
test voltage	2000 V
material isolation body	PA 4.6, GF
temperature range	-40°C... +163°C (260 °C / 10 s)
class of flammability	UL 94 V-0
insulation resistance	>10 ¹² Ω
connection type	soldering
version	low profile
reflow solderable	yes

Fischer Elektronik GmbH & Co. KG
 Nottebohmstraße 28, D - 58511 Lüdenscheid
 ☎: +49 (0) 23 51 / 4 35 - 0, info@fischer elektronik.de







[Sitemap](#)
[Masthead](#)