


FEATURES

Small surface mounting type
Low reverse current and low forward voltage
High reliability

MARKING: E

SOD-723



DIMENSIONS (mm are the original dimensions)

UNIT	A	b _p	c	D	E	H _E	L _p
mm	0.55 0.49	0.32 0.25	0.15 0.08	1.05 0.95	0.65 0.55	1.45 1.35	0.27 0.13

Maximum Ratings and Electrical Characteristics, Single Diode @Ta=25°C

Parameter	Symbol	Limit	Unit
DC reverse voltage	V _R	30	V
Mean rectifying current	I _O	200	mA
Non-repetitive Peak Forward Surge Current@t=8.3ms	I _{FSM}	500	mA
Power dissipation	P _D	100	mW
Thermal Resistance Junction to Ambient	R _{JA}	1000	°C/W
Operating Junction Temperature Range	T _j	-40 ~ +125	°C
Storage Temperature Range	T _{stg}	-55 ~ +150	°C

RB520G-30

Electrical Ratings @Ta=25°C

Parameter	Symbol	Min	Typ	Max	Unit	Conditions
Forward voltage	V_F			0.45	V	$I_F=10\text{mA}$
Reverse current	I_R			0.5	μA	$V_R=10\text{V}$

RATING AND VCHARACTERISTIC CURVES(RB520G-30)

