

**Harvatek Surface Mount LED Data Sheet
HT-191UYG-5309**

Official Product	Product: HT-191UYG-5309			Data Sheet No.
Tentative Product	*****			HT-191UYG-5309
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		June 24, 2009	Version of 1.0	Page 1/14

DISCLAIMER	3
PRODUCT SPECIFICATIONS	4
ATTENTION: ELECTROSTATIC DISCHARGE (ESD) PROTECTION	4
LABEL SPECIFICATIONS	5
PRODUCT CHARACTERISTICS	7
ABSOLUTE MAXIMUM RATINGS	7
ELECTRO-OPTICAL CHARACTERISTICS	7
PACKAGE OUTLINE DIMENSION	7
RECOMMENDED SOLDERING PATTERN FOR REFLOW SOLDERING	7
CHARACTERISTIC CURVES FOR UYG	8
CHARACTERISTIC CURVES (RADIATION PATTERN)	8
PACKAGING	9
TAPE DIMENSION	9
REEL DIMENSION	9
PACKING	10
DRY PACK	11
REFLOW SOLDERING	12
PRECAUTIONS	13
REWORKING	13
CLEANING	13
REVISION HISTORY	14

Official Product	Product: HT-191UYG-5309			Data Sheet No.
Tentative Product	*****			HT-191UYG-5309
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		June 24, 2009	Version of 1.0	Page 2/14

DISCLAIMER

HARVATEK reserves the right to make changes without further notice to any products herein to improve reliability, function or design. HARVATEK does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

LIFE SUPPORT POLICY

HARVATEK's products are not authorized for use as critical components in life support devices or systems without the express written approval of the President of HARVATEK or HARVATEK INTERNATIONAL. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Official Product	Product: HT-191UYG-5309			Data Sheet No.
Tentative Product	*****			HT-191UYG-5309
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		June 24, 2009	Version of 1.0	Page 3/14

Product Specifications

Product	Emission Color	Technology	Test Current I_F (mA)	Luminous Intensity I_V (mcd)	Forward Voltage V_F (V)	Orderable Part Number
HT-191UYG	Ultra Bright Yellow Green	AlInGaP	20	71.5 typ	2.0 typ	HT-191UYG-5309
	Specification	Material			Quantity	
Resin	Clear Diffused	Epoxy resin				
Carrier tape	Per EIA 481-1A specs	Conductive black tape			4000pcs per reel	
Reel	Per EIA 481-1A specs	Conductive black				
Label	HT standard	Paper				
Packing bag	220x240mm	Aluminum laminated bag/ no-zipper			One reel per bag	
Carton	HT standard	Paper				

Others:

Each immediate box consists of 5 reels. The 5 reels may not necessarily have the same lot number or the same bin combinations of I_V , λ_D and V_F . Each reel has a label identifying its specification; the immediate box consists of a product label as well.

ATTENTION: Electrostatic Discharge (ESD) protection



The symbol to the left denotes that ESD precaution is needed. ESD protection for GaP and AlGaAs based chips is necessary even though they are relatively safe in the presence of low static-electric discharge. Parts built with AlInGaP, GaN, or/and InGaN based chips are

STATIC SENSITIVE devices. ESD precaution must be taken during design and assembly.

If manual work or processing is needed, please ensure the device is adequately protected from ESD during the process.

Compliance and Certified


ISO9002, QS9000 and ISO14001 Certified

RoHS Compliant



Official Product	Product: HT-191UYG-5309		Data Sheet No.
Tentative Product	*****		HT-191UYG-5309
Specifications are subject to change without notice. Data and drawings herein are copyrighted.	June 24, 2009	Version of 1.0	Page 4/14

Label Specifications

HARVATEK			Date: yyyy/mm/dd
CUSTOMER P/N: 			
HARVATEK P/N: 		QTY: PCS 	
LOT NO: 		QC	
IV BIN:	COLOR BIN:	VF:	

Harvatek P/N:

H T - 1 9 1 UYG - 5309

Series Name	Emitting Color	Customer Code
HT-191 HT: Harvatek 191: 0603 0.6mm series 1.6 (L) x 0.8 (W) x 0.6 (H) mm	UYG: Ultra Bright Yellow Green	5309 Customer Product Code

Lot No.:

1 2 3 4 5 6 7 8 9 10
P 1 2 2 3 0 A - D T

Code 1	Code 2	Code 3	Code 4, 5	Code 6, 7	Code 9	Code 10
	Mfg. Year	Mfg. Month	Mfg. Date	Lots	Resin Color	Packaging
Internal Tracing Code	Z: 2000 1: 2001 2: 2002 3: 2003	1: Jan. 2: Feb. 9: Sep. A: Oct. B: Nov. C: Dec.	1~31/ (30)	01~99, A,B,C...	C: Clear D: Diffused	T: Tape & Reel

Official Product	Product: HT-191UYG-5309	Data Sheet No.
Tentative Product	*****	HT-191UYG-5309
Specifications are subject to change without notice. Data and drawings herein are copyrighted.	June 24, 2009	Version of 1.0
		Page 5/14

■ Luminous Intensity (I_v) Bin:

Bin	Luminous Intensity Range (mcd)		Bin	Luminous Intensity Range (mcd)	
	Minimum	Maximum		Minimum	Maximum
P1	45.0	57.0	P2	57.0	71.5
Q1	71.5	90.0	Q2	90.0	112.5

@20mA / Ta=25°C, Tolerance: ± 10%

■ Wavelength (λ_D) Bin:

Bin	Wavelength Range (nm)	
	Yellow Green (UYG)	
	Min	Max
C	567.5	570.5
D	570.5	573.5

@20mA / Ta=25°C, Tolerance: ± 0.5nm

■ Forward Voltage (V_F) Bin:

Color	Bin Code	Spec. Range
Ultra Bright Yellow Green (UYG)	E5	1.6 – 1.8 V
	E6	1.8 – 2.0 V
	F5	2.0 – 2.2 V
	F6	2.2 – 2.4 V

@20mA / Ta=25°C, Tolerance: ± 0.05 V

Official Product	Product: HT-191UYG-5309			Data Sheet No.
Tentative Product	*****			HT-191UYG-5309
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		June 24, 2009	Version of 1.0	Page 6/14

Product Characteristics

Absolute Maximum Ratings							
Product	Emission Color	P_d (mW)	I_F (mA)	I_{FP}^* (mA)	V_R (V)	T_{OP} (°C)	T_{ST} (°C)
HT-191UYG	Ultra Bright Yellow Green	72	30	100	5	-30°C~+85°C	-40°C~+90°C

* Condition for I_{FP} is pulse of 1/10 duty and 0.1msec width

Electro-Optical Characteristics									
(T _a 25 °C)									

Product	Emission Color	I_F (mA)	V_F (V)		λ (nm)			I_v (mcd)	
			typ	max	λ_D	λ_P	$\Delta\lambda$	min	typ
HT-191UYG	Ultra Bright Yellow Green	20	2.0	2.4	573	574	20	45	71.5

* Per NIST standards

Package Outline Dimension
Recommended Soldering Pattern for Reflow Soldering


Unit: mm Tolerance: +/-0.1

Outline Dimension	Solder Pattern
Soldering terminals may shift in the x, y direction.	Unit: mm


Official Product	Product: HT-191UYG-5309	Data Sheet No.
Tentative Product	*****	HT-191UYG-5309
Specifications are subject to change without notice. Data and drawings herein are copyrighted.	June 24, 2009	Version of 1.0
		Page 7/14

Characteristic Curves for UYG


Forward Current vs. Ambient Temperature



Forward Voltage vs. Forward Current




Relative Intensity vs. Forward Current




Relative Intensity vs. Ambient Temperature

Plused 20mA, 300us pulse, 10ms period




Relative Intensity vs. Wavelength




Characteristic Curves (Radiation Pattern)

Directive Characteristics




Directive Characteristics



Official Product	Product: HT-191UYG-5309	Data Sheet No.
Tentative Product	*****	HT-191UYG-5309
Specifications are subject to change without notice. Data and drawings herein are copyrighted.	June 24, 2009	Version of 1.0
		Page 8/14

Packaging


Tape Dimension



Part No.	Dim. A	Dim. B	Dim. C	Q'ty/Reel
HT-191UYG	1.80±0.10	0.95±0.10	0.75±0.10	4K


Unit: mm

Reel Dimension



Official Product	Product: HT-191UYG-5309	Data Sheet No.
Tentative Product	*****	HT-191UYG-5309
Specifications are subject to change without notice. Data and drawings herein are copyrighted.	June 24, 2009	Version of 1.0
		Page 9/14

Packing



5 boxes per carton is available depending on shipment quantity.

	Specification	Material	Quantity
Carrier tape	Per EIA 481-1A specs	Conductive black tape	4000pcs per reel
Reel	Per EIA 481-1A specs	Conductive black	
Label	HT standard	Paper	
Packing bag	220x240mm	Aluminum laminated bag/ no-zipper	One reel per bag
Carton	HT standard	Paper	Non-specified
Others:			
Each immediate box consists of 5 reels. The 5 reels may not necessarily have the same lot number or the same bin combinations of Iv, λ_D and Vf. Each reel has a label identifying its specification; the immediate box consists of a product label as well.			


Official Product	Product: HT-191UYG-5309		Data Sheet No.
Tentative Product	*****		HT-191UYG-5309
Specifications are subject to change without notice. Data and drawings herein are copyrighted.	June 24, 2009	Version of 1.0	Page 10/14

Dry Pack

All SMD optical devices are **MOISTURE SENSITIVE**. Avoid exposure to moisture at all times during transportation or storage. Every reel is packaged in a moisture protected anti-static bag. Each bag is properly sealed prior to shipment.

Upon request, a humidity indicator will be included in the moisture protected anti-static bag prior to shipment.

The packaging sequence is as follows:




Official Product	Product: HT-191UYG-5309			Data Sheet No.
Tentative Product	*****			HT-191UYG-5309
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		June 24, 2009	Version of 1.0	Page 11/14


Reflow Soldering

- Recommended tin glue specifications: melting temperature in the range of 178~192 °C
- The recommended reflow soldering profile is as follows (temperatures indicated are as measured on the surface of the LED resin):

Lead Solder Profile



Lead-free Solder Profile



Official Product	Product: HT-191UYG-5309	Data Sheet No.
Tentative Product	*****	HT-191UYG-5309
Specifications are subject to change without notice. Data and drawings herein are copyrighted.	June 24, 2009	Version of 1.0
		Page 12/14

Precautions

1. Avoid exposure to moisture at all times during transportation or storage.
2. Anti-Static precaution must be taken when handling GaN, InGaN, and AlInGaP products.
3. It is suggested to connect the unit with a current limiting resistor of the proper size. Avoid applying a reverse voltage beyond the specified limit.
4. Avoid operation beyond the limits as specified by the absolute maximum ratings.
5. Avoid direct contact with the surface through which the LED emits light.
6. If possible, assemble the unit in a clean room or dust-free environment.

Reworking

- Rework should be completed within 5 seconds under 260 °C.
- The iron tip must not come in contact with the copper foil.
- Twin-head type is preferred.

Cleaning

Following are cleaning procedures after soldering:

- An alcohol-based solvent such as isopropyl alcohol (IPA) is recommended.
- Temperature x Time should be 50°C x 30sec. or <30°C x 3min
- Ultra sonic cleaning: < 15W/ bath; bath volume ≤ 1liter
- Curing: 100 °C max, <3min

Cautions of Pick and Place

- Avoid stress on the resin at elevated temperature.
- Avoid rubbing or scraping the resin by any object.
- Electro-static may cause damage to the component. Please ensure that the equipment is properly grounded. Use of an ionizer fan is recommended.

Official Product	Product: HT-191UYG-5309			Data Sheet No.
Tentative Product	*****			HT-191UYG-5309
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		June 24, 2009	Version of 1.0	Page 13/14

Revision History

Changes since last revision	Page	Version No.	Revision Date
Initial Release – 5309		1.0	06-24-2009

Official Product	Product: HT-191UYG-5309		Data Sheet No.
Tentative Product	*****		HT-191UYG-5309
Specifications are subject to change without notice. Data and drawings herein are copyrighted.	June 24, 2009	Version of 1.0	Page 14/14