



[Sitemap](#)
[Masthead](#)


 english
 

[HOME](#)
[PRODUCTS](#)
[CATALOGUE](#)
[COMPANY](#)
[LATEST NEWS](#)
[SERVICE](#)
[CONTACT](#)
[0 ARTICLES](#)

You are here: [Products](#) » [Connectors f.con](#) » [PCB connectors](#) » [Male headers](#) » [SL 11 SMD ...](#) » [SL 11 SMD 130](#)

Male headers

SL 11 SMD ...

SL 11 SMD 130 34 Z
packing: bulk goods inside cardboard

[add to request](#)




[Features](#)
[Technical Drawing](#)
[Equipping](#)
[Variants](#)
[Accessories / related products](#)

no. of contacts	34
contact material	CuSn alloy
surface contact / contact sleeve	Ni+min.0.2µm Au
surface of contact	tin-plated
volume resistivity	≤5 mΩ
nominal current	3 A
nominal voltage	250 V AC
test voltage	2000 V
material isolation body	PA 4.6, GF
temperature range	-40 °C ... +163 °C (260 °C / 10 s)
class of flammability	UL 94 V-0
insulation resistance	>10 ¹² Ω
connection type	SMD
reflow solderable	yes
packing	bar magazine pick and place pad and bar magazine

Fischer Elektronik GmbH & Co. KG
Nottebohmstraße 28, D - 58511 Lüdenscheid
☎: +49 (0) 23 51 / 4 35 - 0, info@fischer elektronik.de







[Sitemap](#)
[Masthead](#)