



Relays & Contactors > Relays > Signal Relays > Cradle S Signal Relay V23054



Contact Arrangement: 4 Form C 4PDT-CO

Coil Magnetic System: Monostable

Contact Current Rating: 2 A

Performance Type: Standard

Product Mount Type: Socket

[All Cradle S Signal Relay V23054 \(1\)](#)

Features

Configuration Features

Contact Arrangement	4 Form C 4PDT-CO
Contact Number of Poles	6

Electrical Characteristics

Insulation Initial Dielectric Between Open Contacts	500 Vrms
Contact Limiting Making Current	2 A
Contact Limiting Short-Time Current	2 A
Contact Limiting Continuous Current	2 A
Insulation Initial Dielectric Between Adjacent Contacts	500 Vrms
Insulation Initial Dielectric Between Contacts & Coil	500 Vrms
Insulation Initial Resistance	1000 MΩ
Input Voltage	125 VAC
Contact Limiting Breaking Current	2 A
Coil Resistance	630 Ω
Contact Current Rating	2 A
Contact Voltage Rating	150 VDC
Coil Power Rating DC	1 W
Coil Voltage Rating	24 VDC
Contact Switching Voltage (Max)	125 VAC



Body Features

Product Weight	27 g[.952 oz]
----------------	---------------

Contact Features

Contact Plating Material	Gold Flash
Contact Material	Nickel

Termination Features

Relay Connection Type	Plug-In
-----------------------	---------

Mechanical Attachment

Product Mounting Feature Type	Mounting Studs
Product Mount Type	Socket

Dimensions

Product Width	19 mm[.748 in]
Product Length	35 mm[1.37 in]
Product Height	30 mm[1.18 in]

Usage Conditions

Environmental Category of Protection	RTI
Environmental Ambient Temperature (Max)	70 °C[158 °F]
Operating Temperature Range	-40 – 70 °C

Operation/Application

Current Type	DC
Coil Magnetic System	Monostable
Performance Type	Standard

Packaging Features

Packaging Method	Box & Carton
------------------	--------------

Other

Length Class (Mechanical)	30 – 35 mm
Environmental Ambient Temperature Class	50 – 70 °C
Height Class (Mechanical)	25 – 30 mm
Coil Power Rating Class	.8 – 1 W
Width Class (Mechanical)	16 – 20 mm
Contact Current Class	0 – 2 A



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts



Also in the Series | [Axicom Cradle Relay S](#)



Customers Also Bought



Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_3-1393813-6_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_3-1393813-6_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_3-1393813-6_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Product Specification

English



Definitions General Purpose Relays

English