



Product: [77812WS](#)

MachFlex™, 12+G C #18 Str BC, PVC Ins, OA TC Brd, PVC Jkt, PVC Jkt, AWM 2587

[Request Sample](#)

Product Description

MachFlex™ for High Flex, 12+G Conductor 18AWG (105(7x15)x38) Bare Copper, PVC Insulation, Overall Tinned Copper Braid(85%) Shield, PVC Inner Jacket, PVC Outer Jacket, AWM 2587

Technical Specifications

Physical Characteristics (Overall)

| Conductor        |     |           |                  |                   |
|------------------|-----|-----------|------------------|-------------------|
| Element          | AWG | Stranding | Material         | No. of Conductors |
| Conductor(s)     | 18  | 105x38    | BC - Bare Copper | 11                |
| Ground           | 18  | 105x30    | BC - Bare Copper | 1                 |
| Conductor Count: |     |           |                  | 12                |

| Insulation   |                          |                  |                        |
|--------------|--------------------------|------------------|------------------------|
| Element      | Material                 | Nominal Diameter | Nominal Wall Thickness |
| Conductor(s) | PVC - Polyvinyl Chloride | 0.096 in         | 0.022 in               |
| Ground       | PVC - Polyvinyl Chloride |                  |                        |

| Color Chart      |  |
|------------------|--|
| Color            |  |
| Red and Numbered |  |

| Inner Jacket             |                  |                        |
|--------------------------|------------------|------------------------|
| Material                 | Nominal Diameter | Nominal Wall Thickness |
| PVC - Polyvinyl Chloride | 0.480 in         | 0.030 in               |

| Outer Shield |                    |              |
|--------------|--------------------|--------------|
| Type         | Material           | Coverage [%] |
| Braid        | Tinned Copper (TC) | 85%          |

| Outer Jacket             |                  |                        |
|--------------------------|------------------|------------------------|
| Material                 | Nominal Diameter | Nominal Wall Thickness |
| PVC - Polyvinyl Chloride | 0.634 in         | 0.060 in               |

Electrical Characteristics

| Conductor DCR         |                          |
|-----------------------|--------------------------|
| Nominal Conductor DCR | Nominal Outer Shield DCR |
| 6.4 Ohm/1000ft        | 1.6 Ohm/1000ft           |

| Capacitance                             |  |
|-----------------------------------------|--|
| Nom. Capacitance Conductor to Conductor |  |
| 45 pF/ft                                |  |

| Inductance         |  |
|--------------------|--|
| Nominal Inductance |  |

|           |
|-----------|
| .19 µH/ft |
|-----------|

Voltage

|                   |
|-------------------|
| UL Voltage Rating |
| 600 V             |

Temperature Range

|                              |                                                |
|------------------------------|------------------------------------------------|
| UL Temp Rating:              | 90°C                                           |
| Operating Temperature Range: | -40°C To 90°C (Static), -5°C To 90°C (Flexing) |

Mechanical Characteristics

|                                        |                   |
|----------------------------------------|-------------------|
| Oil Resistance:                        | Yes               |
| Flex Cycle Rating:                     | 14 Million Cycles |
| Bulk Cable Weight:                     | 497 lbs/1000ft    |
| Max. Pull Tension:                     | 174 lbs           |
| Min. Bend Radius (Continuous Flexing): | 5.1 in            |
| Min. Bend Radius/Minor Axis:           | 5.1 in            |

Standards

|                          |                     |
|--------------------------|---------------------|
| UL AWM Style Compliance: | AWM 2587, AWM 10012 |
| CSA AWM Compliance:      | AWM I/II A/B        |

Applicable Environmental and Other Programs

|                                              |                               |
|----------------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV):               | Yes                           |
| EU Directive 2003/11/EC (BFR):               | Yes                           |
| EU Directive 2011/65/EU (RoHS 2):            | Yes                           |
| EU Directive 2012/19/EU (WEEE):              | Yes                           |
| EU Directive 2015/863/EU (RoHS 2 amendment): | Yes                           |
| EU Directive Compliance:                     | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                                  | Yes                           |

Suitability

|                               |     |
|-------------------------------|-----|
| Suitability - Oil Resistance: | Yes |
|-------------------------------|-----|

Flammability, LS0H, Toxicity Testing

|                    |           |
|--------------------|-----------|
| CSA Flammability:  | FT1       |
| UL voltage rating: | 600 V RMS |

Related Part Numbers

Variants

| Item #         | Color | Put-Up Type | UPC          |
|----------------|-------|-------------|--------------|
| 77812WS 010100 | Black | Reel        | 612825412434 |

History

|                      |                                                  |
|----------------------|--------------------------------------------------|
| Update and Revision: | Revision Number: 0.140 Revision Date: 05-31-2024 |
|----------------------|--------------------------------------------------|

© 2024 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.