



Part Number : 1554216004
Product Description : Flamar Ethernet 5e Network Cable, WSOR Jacket, Braided Shielding Overall, 8 Circuits, 4x(2x0.14mm²) / 4x(2x26 AWG), 7.20mm (.283") Diameter, 300.0m (984.25') Length, Teal
Series Number : 155421
Status : Active
Product Category : Industrial Cable
Engineering Number : 3X100M



Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
--------	--------

Category	Industrial Cable
Series	155421
Description	Flamar Ethernet 5e Network Cable, WSOR Jacket, Braided Shielding Overall, 8 Circuits, 4x(2x0.14mm ²) / 4x(2x26 AWG), 7.20mm (.283") Diameter, 300.0m (984.25') Length, Teal
Comments	3 reels of 100.0m each
Geographic Area	Global
Product Family	Flamar Standard and Custom Cables for Industrial Automation
Product Name	Flamar,Network
Protocol	EtherNet 5e
UPC	889056464949

Agency

UL	E172949
----	---------

Electrical

Current - Maximum per Contact	Contact Molex
Voltage - Maximum	600V

Physical

Bending Radius - Minimum	> 15xOD
Cable Length	300.0m
Circuits (Loaded)	8
Color - Cable Jacket	Teal
Insulation	PE
Material - Outer Jacket	WSOR
Net Weight	0.065/kg
Outer Jacket Diameter	7.20mm
Packaging Type	Reel
Temperature Range - Operating	-10° to +60°C
Wire/Cable Type	UL AWM 21215 / CSA
Wire Size (AWG)	26
Wire Size mm ²	0.14

Use with Part(s)

Description	Part Number
Micro-Change (M12) Field Attachable Connectors	<u>120071</u>
Micro-Change (M12) Field Attachable Connectors and D-Sub Connectors	<u>120100</u>
Micro-Change (M12) and Mini-Change Trunk and Drop Connectors	<u>130034</u>
Field Attachable Connectors	<u>130047</u>

This document was generated on Sep 23, 2024