




MATERIAL NO.	ENGINEERING NO.	LENGTH	POLES
1206140003	LW03006K05M020	78.7 (2M)	3
1206140004	LW05006K05M020	78.7 (2M)	5
1206140006	LW04006K05M020	78.7 (2M)	4

NOTICE: THIS PART IS CSA AND FACTORY MUTUAL APPROVED
NO CHANGES CAN BE MADE TO THE ASSEMBLY, COMPONENTS
OR SUPPLIER WITHOUT PRIOR APPROVAL FROM CSA AND
FACTORY MUTUAL.



ISO2
Scale 1:1



- NOTES:
1. MATERIAL: SEE TABLE
 2. FINISHES: SEE TABLE
 3. PRODUCT SPECIFICATIONS: PS-120614-001
 4. CONTROL DOC: ES-120614-001
 5. 3 & 4 POLE ELECTRICAL SPECIFICATIONS:
VOLTAGE RATING: 125V
CURRENT RATING: 4 AMPS
 6. 5 POLE ELECTRICAL SPECIFICATIONS:
VOLTAGE RATING: 32V
CURRENT RATING: 4 AMPS

② LW0X006K05MXXX

SINGLE END
POLE QTY.
HEAD STYLE
CABLE TYPE
FINISHED LENGTH
REF. XXX = METERS
EXAMPLE 010= 1M

MALE FACE VIEW

3 POLE	4 POLE	5 POLE
1 BROWN 3 BLUE 4 BLACK	1 BROWN 2 WHITE 3 BLUE 4 BLACK	1 BROWN 2 WHITE 3 BLUE 4 BLACK 5 GRAY

ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH
8	1	WRAP LABEL	PLASTIC FILM	BLACK/YELLOW
7	1	FLAG LABEL (WARNING)	POLYESTER	BLACK/ORANGE
6	1	OVERMOLD	TPE	YELLOW
5	1	OUTER SLEEVE	ST. STEEL	PASSIVATED
4	1	INNER SLEEVE	ST. STEEL	PASSIVATED
3	XX	CONTACT	Cu ALLOY	GOLD PLATED
2	1	INSERT	PUR	BLACK
1	1	CABLE, #22 AWG ITC/PLTC	TPE	YELLOW


REV	DESCRIPTION
B	ADDED P/N LEGEND EC NO: IPG2014-0138 DRAWN: RSTONE 2013/07/23 CHKD: B. WOODMAN 2013/08/01 APPR: B. WOODMAN 2013/12/30

QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)
▽=0	mm INCH
▽=0	4 PLACES ± --- ± ---
	3 PLACES ± --- ± ---
	2 PLACES ± --- ± .01
	1 PLACE ± 0.3 ± ---
	ANGULAR ± 2 °
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS


DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
IN/MM	15:1	INCH	
DRAWN BY	DATE	TITLE	
RSTONE	2011/11/21	ULTRA-LOCK ZONE 2 MALE, STRAIGHT K05, 22 AWG, TPE	
CHECKED BY	DATE		
L. HARTMANN	2012/01/27		
APPROVED BY	DATE		
JFMURPHY	2012/04/18		
MATERIAL NO.	DOCUMENT NO.		
SEE CHART	SD-120614-009		
SIZE			
C			

CLASS 1, DIVISION 2, GROUP A, B, C, OR D
HAZARDOUS LOCATION

NON-HAZARDOUS LOCATION




LWR X 006 A18 CXXX
(MALE 1/2" NPT)
LWR X A06 A18 CXXX
(MALE 1/4" NPT)



LW8 X 032 XXX M XXX




LW8 X 030 XXX M XXX




LWW X 032 XXX M XXX




LWW X 030 XXX M XXX




MALE ENDS




LW8 X 033 XXX M XXX



LW8 X 031 XXX M XXX



LWW X 033 XXX M XXX



LWW X 031 XXX M XXX

NOTES:


1. THE INSTALLATION MUST BE IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE (NEC), ANSI/NFPA 70. SPECIFIC REQUIREMENTS FOR THE INSTALLATION OF ITC RATED CABLE MAY BE FOUND IN ARTICLE 501.4(B)(1)(5) AND ARTICLE 727.4
2. THE MOLDED CONSTRUCTION OF THE CORDSET AND GAS/VAPORTIGHT CONTINUOUS SHEATH OF THE CABLE MEET THE REQUIREMENTS OF THE NEC, ARTICLE 501-5(E)(2) FOR CABLE SEALS IN CLASS 1, DIVISION 2

FIELD DEVICE APPROVAL FOR CLASS 1, DIV. 2
OR CLASS 1, ZONE2 INSTALLATIONS


REF. SEE SHEET 3 FOR CONFIGURATION INFORMATION

CLASS 1, DIVISION 2, GROUP A, B, C, OR D
HAZARDOUS LOCATION


NON-HAZARDOUS LOCATION



LWR X 000 A18 CXXX
(FEMALE 1/2" NPT)
LWR X A00 A18 CXXX
(FEMALE 1/4" NPT)



8LW X 031 XXX M XXX




8LW X 030 XXX M XXX




WLW X 031 XXX M XXX



WLW X 030 XXX M XXX



FEMALE ENDS



8LW X 033 XXX M XXX



8LW X 032 XXX M XXX



WLW X 033 XXX M XXX



WLW X 032 XXX M XXX






NOTICE: THIS PART IS CSA AND FACTORY MUTUAL APPROVED
NO CHANGES CAN BE MADE TO THE ASSEMBLY, COMPONENTS
OR SUPPLIER WITHOUT PRIOR APPROVAL FROM CSA AND
FACTORY MUTUAL.

THIS DRAWING SUPERSEDES ES-120614-001 REV-B

SEE SHEET 3 EC NO: IPG2018-0141 G DRAWN: RSTONE CHKD: BWOODMAN APPR: BWOODMAN	REV	DESCRIPTION	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM		SCALE 1:1	DESIGN UNITS INCH	 THIRD ANGLE PROJECTION
						DRAWN BY DATE RSTONE 2012/05/18		TITLE CONTROL DOC FOR ULTRA-LOCK ZONE 2		
				4 PLACES ± --- ± ---		CHECKED BY DATE K JOZWIK 2012/05/22		MOLEX INCORPORATED		
				3 PLACES ± --- ± ---		APPROVED BY DATE JFMURPHY 2012/08/27				
				2 PLACES ± --- ± ---		MATERIAL NO. 1206149999		DOCUMENT NO. SD-120614-999		SHEET NO. 1 OF 3
				1 PLACE ± --- ± ---		SIZE C		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
ANGULAR ± ---°										
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS								

CLASS 1, DIVISION 2, GROUP A, B, C, OR D
HAZARDOUS LOCATION

HAZARDOUS LOCATION



REF:

1. SEE SHEET 1 FOR NOTES
2. SEE SHEET 3 FOR CONFIGURATION INFORMATION

NOTICE: THIS PART IS CSA AND FACTORY MUTUAL APPROVED
NO CHANGES CAN BE MADE TO THE ASSEMBLY, COMPONENTS
OR SUPPLIER WITHOUT PRIOR APPROVAL FROM CSA AND
FACTORY MUTUAL.

SEE SHEET 3 EC NO: IPG2018-0141 2017/08/28 DRWN:RSTONE 2017/08/30 CHKD:WOODMAN 2017/09/06 APPR:WOODMAN	DESCRIPTION REV	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM		SCALE 1:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION		
				mm	INCH	DRAWN BY RSTONE	DATE 2012/05/18	CONTROL DOC FOR ULTRA-LOCK ZONE 2			
			4 PLACES	± ---	± ---	CHECKED BY K JOZWIK	DATE 2012/05/22				
			3 PLACES	± ---	± ---	APPROVED BY JFMURPHY	DATE 2012/08/27				
			2 PLACES	± ---	± ---	MATERIAL NO. 1206149999		DOCUMENT NO. SD-120614-999		SHEET NO. 2 OF 3	
			1 PLACE	± ---	± ---	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS					
			ANGULAR ± ---°		MOLEX MOLEX INCORPORATED						
			SIZE C		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION						

M12/MICROCHANGE ULTRA-LOCK CORD CONNECTORS AND CORD SETS

LWO 3 000 C02 M 020 8
I II III IV V VI VII

I: CONNECTOR TYPE

LWO= ULTRA-LOCK ZONE 2 MALE OR FEMALE SINGLE END CORDSET
LWV= ULTRA-LOCK ZONE 2 FEMALE TO STANDARD ULTRA-LOCK MALE DOUBLE ENDED CORDSET
WLW= ULTRA-LOCK ZONE 2 MALE TO STANDARD ULTRA-LOCK FEMALE DOUBLE ENDED CORDSET
LW8= ULTRA-LOCK ZONE 2 FEMALE TO STANDARD M12 MALE DOUBLE ENDED CORDSET
8LW= ULTRA-LOCK ZONE 2 MALE TO STANDARD M12 FEMALE DOUBLE ENDED CORDSET
LWLW= ULTRA-LOCK ZONE 2 FEMALE TO ULTRA-LOCK ZONE 2 MALE DOUBLE ENDED CORDSET

II: NUMBER OF POLES: 3= 3 PIN, 4= 4 PIN, 5 = 5 PIN

III: CONFIGURATION

SINGLE ENDED:
000= STRAIGHT FEMALE CONNECTOR
001= FEMALE 90°
006= STRAIGHT MALE, EXTERNAL THREAD
007= MALE 90°

DOUBLE ENDED:
030= STRAIGHT FEMALE CONNECTOR TO STRAIGHT MALE CONNECTOR
031= FEMALE 90° TO MALE STRAIGHT
032= FEMALE STRAIGHT TO MALE 90°
033= FEMALE 90° TO MALE 90°

IV: CABLE TYPE

C02= SJ00W YELLOW, 18 AWG, DC CODE (CSA ONLY) 
K03= PLTC/ITC, 18 AWG, TPE JACKET
K05= PLTC/ITC, 22 AWG, TPE JACKET

V: UNIT OF MEASURE

F= FEET
M= METERS

VI: CABLE LENGTH (MAY BE ANY 3 DIGIT NUMBER FROM 001-100)

1ST DIGIT= 10 X LENGTH
2ND DIGIT= 1 X LENGTH
3RD DIGIT= .1 X LENGTH

VII: COUPLING NUT MATERIAL

ULTRA-LOCK ZONE 2 END(S) ARE STAINLESS STEEL

M12 OR ULTRA-LOCK:

NONE = STANDARD MATERIAL (NICKEL PLATED BRASS)
8= STAINLESS STEEL

NOTICE: THIS PART IS CSA AND FACTORY MUTUAL APPROVED
NO CHANGES CAN BE MADE TO THE ASSEMBLY, COMPONENTS
OR SUPPLIER WITHOUT PRIOR APPROVAL FROM CSA AND
FACTORY MUTUAL.

M12/MICROCHANGE ULTRA-LOCK OUTLETS

LWR 3 A00 A18 M 020 8
I II III IV V VI VII

I: CONNECTOR TYPE

LWR= LOCKING INLETS AND OUTLETS

II: NUMBER OF POLES 3=3 PIN, 4= 4 PIN, & 5= 5 PIN

III: CONFIGURATION

SINGLE ENDED:
A00= FEMALE STRAIGHT (INT.THEAD) 1/4-18 NPT
A06= MALE STRAIGHT (EXT.THEAD) 1/4-18 NPT
000= FEMALE STRAIGHT (INT.THEAD) 1/2-14 NPT
006= MALE STRAIGHT (EXT.THEAD) 1/2-14 NPT

 IV: WIRE TYPE

A18= 22 AWG, PVC, DC COLOR CODE, UL TYPE 1061
A16= 18 AWG, PVC, DC COLOR CODE, UL TYPE 1569

V: UNIT OF MEASURE

A= INCHES
F= FEET
C= CENTIMETERS
M= METERS

VI: WIRE LENGTH (MAY BE ANY 3 DIGIT NUMBER FROM 001-100)

1ST DIGIT= 10 X LENGTH
2ND DIGIT= 1 X LENGTH
3RD DIGIT= .1 X LENGTH

VII: SHELL MATERIAL

M12 OR ULTRA-LOCK:
NONE = STANDARD MATERIAL (COPPER ZINC ALLOY)
3= NICKEL PLATED BRASS
8= STAINLESS STEEL

CORSET NOTE IV: ADD CSA OUTLET NOTE IV: REMOVE PCB PINS EC NO: IPG2018-0141 G DRWNR:RSTONE 2017/08/28 CHKD:RWOODMAN 2017/08/30 APPR:RWOODMAN 2017/09/06	REV	DESCRIPTION	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM		SCALE 1:1	DESIGN UNITS INCH	 THIRD ANGLE PROJECTION	CONTROL DOC FOR ULTRA-LOCK ZONE 2  MOLEX INCORPORATED	SHEET NO. 3 OF 3					
				mm	INCH	DRAWN BY	DATE	1206149999		SD-120614-999							
				4 PLACES	± ---	± ---	RSTONE						2012/05/18				
				3 PLACES	± ---	± ---	CHECKED BY						DATE				
				2 PLACES	± ---	± ---	K JOZWIK						2012/05/22				
				1 PLACE	± ---	± ---	APPROVED BY						DATE				
				ANGULAR ± ---°		MATERIAL NO.	JFMURPHY 2012/08/27										
				DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS						SIZE B			THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				