SPECIFICATION

100

CIRCULAR CONNECTORS

Push-pull connectors female fixed socket CCM series


CCM2S1/07 7 pole

- Premium range of circular connectors
- IP68 sealed using vacuum technology (when connected and using environmental cable clamp)
- Tough, high performance interconnection solution
- Compact panel mounting design
- · Ideal for harsh and extreme environments
- Suitable for broadcasting, autosport, military, rail, marine, security, industrial and agricultural applications
- Key coded to prevent misconnection
- Will not disconnect when the cable is under load or stress
- · Tool slots for secure and tight mounting
- Tested to IEC 60512-3-5a



SOCKETS

| PART NO. | DESCRIPTION | POLES | SERIES |
|-----------|---------------------|-------|---------------|
| CCM2S1/07 | Female fixed socket | 7 | CCM series |



| Shell style/model | DEU type fixed socket, female contact | |
|-------------------------|--|--|
| Codes | Code 1 | |
| Contact type | Solder type | |
| Contact diameter | 0.7mm | |
| Max. stranded conductor | AWG 21-22 | |
| Max diameter | 0.79mm | |
| Vtest (contact-shell) | 1000V(AC) 2000V(DC) | |
| Vtest (contact-contact) | 1300V(AC) 2000V(DC) | |
| Rated current | 5.0A | |
| Rated voltage | ≤250V | |
| Mechanical operation | 5000 mating cycles | |
| Housing material | Brass (natural chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces | |
| Insulator | PPS | |
| Contacts | Brass (gold plated) | |
| Humidity (max) | <=95% [at 60°C /140°F] | |
| Vibration | 15g [10 Hz - 2000 Hz] | |
| Shock resistance | 100g [6 ms] | |
| Salt spray corrosion | >72 hr | |
| Climatical category | 50/175/21 | |
| Shielding (min) | 75 dB (10 MHz) | |
| Shielding (min) | 40 dB (1 GHz) | |
| IP rating | IP68 (when connected and using environmental cable clamp) | |

KEY FEATURES

Key coded | Panel mounting socket | Flat face | Face slots for tightening with a tool

ACCESSORIES

Metal and rubber caps for sockets

| PART NO. | DESCRIPTION | |
|----------|----------------------------------|--|
| CCT21 | Camcirc metal cap for sockets A2 | |

| T21 | Camcirc metal cap for sockets A2 | |
|-----|----------------------------------|--|

| DESCRIPTION | |
|-----------------------------------|--|
| Camcirc rubber cap for sockets A2 | |
| | |
| | |



ASSOCIATED PRODUCTS

CCA2P1/A07

- CCA Series A2 size plug

page 111

