# RLP73K3AR18JTDG ACTIVE

### CGS | CGS RLP73

TE Internal #: 3-2176058-1

Current Sensing Resistor, Thick Film, 2512, 2 W, .18 ohm, 5 %, ±200 ppm/°C, Solder, 2 Termination, Height .74 mm [.029 in], CGS RLP73

View on TE.com >



Passive Components > Resistors > Surface Mount Resistors > Thick Film Resistor: Current Sense



Resistor Type: Current Sensing Resistor

Element Type: **Thick Film**Package Size Code: **2512** 

Power Rating: 2WResistance Value:  $.18 \Omega$ 

All Thick Film Resistor: Current Sense (154)

## Features

#### **Product Type Features**

Froduct Type Features	
Resistor Type	Current Sensing Resistor
Element Type	Thick Film
Package Size Code	2512
Configuration Features	
Number of Resistors	1
Electrical Characteristics	
Power Rating	2 W
Resistance Value	.18 Ω
Resistance Class	Up to $1k\Omega$
Passive Component Tolerance	5 %
Termination Features	
Surface Mount Resistor Termination Type	Solder

2

Number of Terminations



#### **Dimensions**

Product Height	.74 mm[.029 in]
Product Length	6.35 mm[.25 in]
Product Width	3.15 mm[.124 in]

#### **Usage Conditions**

Temperature Coefficient	±200 ppm/°C	

#### **Packaging Features**

Packaging Method	Taped & Reeled

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


## **Compatible Parts**







## Also in the Series | CGS RLP73



# Customers Also Bought















### **Documents**

Product Drawings
RLP73K 3A R18 5% 2K RL

English

**CAD Files** 

3D PDF

3D

Current Sensing Resistor, Thick Film, 2512, 2 W, .18 ohm, 5 %, ±200 ppm/°C, Solder, 2 Termination, Height .74 mm [.029 in], CGS RLP73



**Customer View Model** 

ENG\_CVM\_CVM\_3-2176058-1\_BA.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_3-2176058-1\_BA.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_3-2176058-1\_BA.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

SMD Low Ohmic Current Sense Resistors - Type RL73 Series

English