










A4001WR-S-2P-1

A4001WR-S-2P-2

A4001WR-S-2P-3

A4001WR-S-3P





A4001WR-S-4P-137

A4001WR-S-4P-157

A4001WR-S-4P

A4001WR-S-5P



SPECIFICATIONS:

Current Rating: 1A AC,DC
Voltage Rating: 600V AC,DC
Temperature Range: -40°C ~ +105°C
Contact Resistance: 10mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 1800V AC/minute
PIN Material: Brass/Tin over Nickel
Solder PIN Material: Brass/Tin over Nickel
Material: Nylon 6T,UL94V-0(Beige)

Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2P-1	4.00	10.00	6.50	4P-137	12.00	18.00	14.50
2P-2	8.00	14.00	10.50	4P-157	12.00	18.00	14.50
2P-3	12.00	18.00	14.50	4P	12.00	18.00	14.50
3P	8.00	14.00	10.50	5P	16.00	22.00	18.50

CJTconn CHANGJIANG CONNECTORS CO.,LTD.				
Unit	Scale	Sheet	TITLE	
mm	1:1	1 of 1	4.00mm Pitch Right angle Wafer-SMD Type	
DRAWN	CHK'D	APPR		
Chengbiao Ye	Diankui Wan	Jack Yin		
General Tolerances		THIRD ANGLE PROJECTION		
x.xx±0.25 x.xxx±0.20 x.xxxx±0.15 ANGLES ±1°			DRAWING NO.	REV A3
			A4001WR-S-XP	

A3	CHANGE THE DRAWING	2023.06.14
A2	CHANGE THE DRAWING	2023.03.02
A1	CHANGE THE DRAWING	2019.02.21
A0	NEW RELEASE	2005.05.10
REV	DESCRIPTION	DATE