



Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Assembly Type: **PCB Mount Header**

PCB Mount Orientation: **Right Angle**

Connector System: **Board-to-Board**

Number of Positions: **80**

Number of Rows: **2**

Features

Product Type Features

PCB Connector Assembly Type	PCB Mount Header
Connector System	Board-to-Board
Header Type	Unshrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Connector Contact Load Condition	Fully Loaded
PCB Mount Orientation	Right Angle
Number of Positions	80
Number of Rows	2
Board-to-Board Configuration	Perpendicular

Electrical Characteristics

Insulation Resistance	5000 MΩ
Dielectric Withstanding Voltage (Max)	750 Vrms

Body Features

Primary Product Color	Black
-----------------------	-------

Contact Features

Mating Square Post Dimension	.64 mm[.025 in]
------------------------------	-----------------



	15 µin
Contact Shape & Form	Square
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Gold Flash
Contact Base Material	Phosphor Bronze
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Material Thickness	.38 µm[15 µin]
Contact Type	Pin
Contact Current Rating (Max)	3 A

Termination Features

Square Termination Post & Tail Dimension	.64 mm[.025 in]
Termination Post & Tail Length	2.79 mm[.11 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Mating Alignment	Without
PCB Mount Retention	Without
PCB Mount Alignment	Without
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	2.54 mm[.1 in]
Housing Material	Thermoplastic

Dimensions

Row-to-Row Spacing	2.54 mm[.1 in]
PCB Thickness (Recommended)	1.4 mm[.055 in]

Usage Conditions

Housing Temperature Rating	Standard
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]

Operation/Application

Circuit Application	Signal
---------------------	--------

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
Compatible With Approved Standards Products	CSA LR7189, UL E28476



UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	25
Packaging Method	Tray

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Wave solder capable to 240°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 1-5535512-3 80 MODII HORZ DR CE EESS .100	 TE Part # 3-5146140-9 80 MODII HORZ DR CE 100CL	 TE Part # 3-5147722-9 80 MODII HORZ DR SFMNT 30AU	 TE Part # 4-5146140-0 82 MODII HORZ DR CE 100CL
--	--	--	--



TE Part # 4-5146140-1
84 MODII HORZ DR CE 100CL



TE Part # 4-5146140-2
86 MODII HORZ DR CE 100CL



TE Part # 4-5146140-3
88 MODII HORZ DR CE 100CL



TE Part # 4-5146140-4
90 MODII HORZ DR CE 100CL



TE Part # 4-5146140-5
92 MODII HORZ DR CE 100CL



TE Part # 4-5146140-6
94 MODII HORZ DR CE 100CL



TE Part # 4-5146140-7
96 MODII HORZ DR CE 100CL



TE Part # 4-5146140-8
98 MODII HORZ DR CE 100CL



TE Part # 4-5146140-9
100 MODII HORZ DR CE 100CL



TE Part # 5-5146140-0
102 MODII HORZ DR CE 100CL



TE Part # 5-5146140-1
104 MODII HORZ DR CE 100CL



TE Part # 5-5146140-2
106 MODII HORZ DR CE 100CL



TE Part # 5-5146140-3
108 MODII HORZ DR CE 100CL



TE Part # 5-5146140-4
110 MODII HORZ DR CE 100CL



TE Part # 5-5146140-5
112 MODII HORZ DR CE 100CL




TE Part # 5-5146140-6
114 MODII HORZ DR CE 100CL


Also in the Series | AMPMODU Headers



Connector Caps & Covers(1)




Connector Contacts(64)




Connector Hardware(2)



PCB Headers & Receptacles(3197)



Customers Also Bought



Documents

- CAD Files

Customer View Model

ENG_CVM_4-87230-0_K.3d_igs.zip

English
- Customer View Model

ENG_CVM_4-87230-0_K.3d_stp.zip

English
- Customer View Model

ENG_CVM_4-87230-0_K.2d_dxf.zip

English
- 3D PDF

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

- Datasheets & Catalog Pages

AMPMODU_INTERCONNECTION_SYSTEM_SECTION5

English

4-87230-0

PCB Mount Header, Right Angle, Board-to-Board, 80 Position, 2.54 mm [.1 in]
Centerline, Unshrouded, Gold, Through Hole - Solder, AMPMODU Headers

