




Outline:

- Magnetic shielded structure:excellent resistance to electro Magnetic interference (EMI)
- A composite structure,ultra low buzz noise
- Low loss,high efficiency,wide application frequency
- Lightweight design,save space,suitable for high density SMT

Features:

- Core material: Alloy powder
- Environmental: RoHS, Reach compliant ,Halogen free
- Weight:2.82g
- Moisture Sensitivity:Level (MSL) 1
(unlimited floor life at 5 ~ 40°C, RH≤ 70% relative humidity).
- Operating temperature range: -40°C ~ +125°C
(including coil's self temperature rise)
- Storage temperature range: -40°C ~ +125°C

Application:

- PDA/notebook/desktop/server applications
- DC /DC converters for entertainment/navigation systems
- Noise suppression for motors:windshield wipers/power seats/Power Mirrors/heating and ventilation blower/ HID lighting


1 Electrical Characteristics

Part No.	Inductance (μ H)×1 ±20%	D.C.R. (m Ω)		Isat (A)×2 Typical	Irms (A) ×3 Typical
		Typical	Max.		
CSAB1050A-R82M	0.82	2.00	2.30	31.0	23.0
CSAB1050A-1R0M	1.00	2.10	2.50	28.5	22.5
CSAB1050A-1R5M	1.50	3.40	4.00	23.5	18.0
CSAB1050A-2R2M	2.20	6.10	7.30	22.0	14.5
CSAB1050A-3R3M	3.30	7.60	9.20	16.0	12.0
CSAB1050A-4R7M	4.70	11.2	13.2	14.0	10.5
CSAB1050A-5R6M	5.60	12.6	15.5	13.5	9.70
CSAB1050A-6R8M	6.80	15.5	18.6	12.0	8.50
CSAB1050A-8R2M	8.20	20.5	24.0	11.0	7.50
CSAB1050A-100M	10.0	24.5	28.0	10.0	6.90
CSAB1050A-150M	15.0	30.5	39.0	8.00	6.00
CSAB1050A-220M	22.0	50.5	60.0	7.00	5.00
CSAB1050A-330M	33.0	73.0	88.0	5.80	4.50
CSAB1050A-470M	47.0	98.5	130	4.50	3.50
CSAB1050A-560M	56.0	123	148	4.20	3.30
CSAB1050A-680M	68.0	134	160	4.00	3.20

All data is tested on 25°C ambient temperature

- 1.Inductance measure condition at 100kHz,1.0V
- 2.Isat:the actual value of DC current when the inductance decrease 30% of its initial value
- 3.Irms:the actual value of DC current when the temperature rise is $\Delta T40^{\circ}\text{C}$ ($T_a=25^{\circ}\text{C}$)

2 Product Dimensions (mm)



3 How to Order:









CSAB1050A-470M









Model _____

Dimensions _____









Value Code _____









4 Saturation Current vs Temperature Rise Current Curve





















5 L vs Frequency





6 Impedance vs Frequency





7.1 Carrier Tape Dimensions (mm)



Cover tape peeling off condition

- Cover tape peeling force shall be 0.1 to 1.3N.
- Reference peeling speed 300±10mm/min.


The diagram illustrates the cover tape peeling process in two stages. The top stage shows a circular reel of tape with a label. A cover tape is being peeled off by a sprocket, with an arrow indicating the 'Unreeling direct' direction. A curved arrow points to the bottom stage, which is a detailed view of the peeling angle. It shows the 'Cover tape' being peeled at an angle of 165°~180° from the 'Carrier tape'. The 'Pull direction' is indicated by an arrow pointing left, and the 'Unreeling direction' is indicated by an arrow pointing right.

■ Outer Carton : 360×360×370mm

8 / 10

8 Soldering Specification

8.1 Reflow Profile for SMT Components



8.2 Classification of Peak Package Body Temperature (T_P)

	Package Thickness	Package Volume		
		<350 mm ³	350 ~ 2000 mm ³	>2000 mm ³
PB-Free Assembly	<1.6mm	260 $^{\circ}\text{C}$	260 $^{\circ}\text{C}$	260 $^{\circ}\text{C}$
	1.6 ~ 2.5mm	260 $^{\circ}\text{C}$	250 $^{\circ}\text{C}$	245 $^{\circ}\text{C}$
	$\geq 2.5\text{mm}$	250 $^{\circ}\text{C}$	245 $^{\circ}\text{C}$	245 $^{\circ}\text{C}$

※ Reflow is referred to standard IPC/JEDEC J-STD-020E.

9 Notice of Use

- 9.1 Special remind:Circuit design, component placement, PCB size and thickness, cooling system and etc. all will affect the product temperature. Please verify the product temperature in the final application.
- 9.2 Product in packing storage condition:temperature 5 ~ 40°C, RH≤ 70%.
If taking out for use, the remaining products should be sealed in plastic bags and preserved in accordance With the above conditions, to avoid oxidation of terminals (electrodes), affecting soldering status.
- 9.3 A storage of Codaca Electronic products for longer than 12 months is not recommended, Within other effects, the terminals may suffer degradation, resulting in bad solderability. Therefore, all products shall be used within the period of 12 months based on the day of shipment.
- 9.4 Do not keep products in unsuitable storage conditions, such as areas susceptible to high temperatures, high humidity, dust or corrosion.
- 9.5 Always handle products with care.
- 9.6 Don't touch electrodes directly with bare hands as oil secretions may inhibit soldering.
Always ensure optimum conditions for soldering.
- 9.7 When this product will be used on a similar or new project to the original one, sometimes it might be unable to satisfy the specifications due to different condition of usage.
- 9.8 This inductor itself does not have any protective function in abnormal condition, such as overload, short-circuit, open-circuit conditions, etc. Therefore, it shall be confirmed that there is no risk of smoke, fire, dielectric withstand voltage, insulation resistance, etc., or use in abnormal conditions protective devices or protection circuit in the end product.
- 9.9 Hi-Pot test with higher voltage than spec value will damage insulating material and shorten its life.
- 9.10 If using in potting compound, the magnet wire coating might be damaged, please consult with us.
- 9.11 Refrain from rinsing product. If necessary, please consult with us.
- *9.12 Codaca Electronic products without "V" prefix are qualified for industrial product requirement , and with "V" prefix are qualified for AEC-Q200, but it doesn't mean that Codaca Electronic products can absolutely meet specific industry norms and quality test standards in automotive electronics or more strict application fields . Codaca Electronic will be exempted from being responsible for the consequences of using Codaca products in automotive electronic or higher application field related to safety when without being aware of it.