

REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2024.9.19	阿树

■SPECIFICATIONS

- Voltage rating:350V AC/DC
- Current rating:4A AC/DC
- Withstanding Voltage:1700V AC/minute
- Temperature range:-40°C~+125°C
- Insulation resistance:≥1000MΩ
- Contact resistance:≤30mΩ
- After environmental testing:≤20mΩ

PART NO.:

X1800 W R S-02 B-LP SW
① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ①Series No
②Category:W-Wafer
③Welding Board Angle:R-Stright 90°
④Welding Way:S-SMT
⑤Row No.Pin No:02-02Pin
⑥Plug the Pin &Special No.: B-With Lock
⑦Material:LP-LCP 94V-0
⑧Planting:SW-Matte Tin Plating

X1800WRS-02B-LPSW	LCP UL 94V-0	Brass	Matte Tin	X1800H-B
PART NO	Material	Material(Pin)	Finish(Pin)	Mates With XKB Terminal

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERANCES	



DESIGN
CHECKED
APPROVED

阿树

VIEW:
UNIT: mm/in
SIZE: A4

MODEL TYPE:
2.54mm Crimp Style Connector
PART NO.:
X1800WRS-02A-LPSW
DWG NO.:

SCALE	PAGE	REVISION
N/A	1/1	A1