


CONFIGURATION		PART NUMBER	LENGTH
Cable Assembly, Molded, 14AWG, Standard Flex, Connectors - Male Straight Entry/ Female Straight Entry		P29008-MXX	AS REQUESTED
DIMENSIONS			
 <p>LENGTH M(meter)</p> <p>WIRING DIAGRAM</p> <p>BLACK 14AWG</p> <p>WHITE 14AWG</p> <p>RFD 14AWG</p> <p>GREEN 14AWG</p> <p>FACE VIEW</p> <p>FACE VIEW</p>			
TECHNICAL DATA			
TEMPERATURE RANGE:	-20C to +90C		
PROTECTION:	IP 67, NEMA 6P		
BODY:	OIL RESISTANT PVC		
CONTACTS:	COPPER ALLOY		
CONTACT PLATING:	GOLD OVER NICKEL PLATING		
CONNECTOR FACE:	PVC BLACK		
AMPERAGE:	15AMP		
COUPLER:	MACHINED ALUMINUM, ANODIZED		
CABLE CHARACTERISTICS:	UL TYPE TC 600V 90°C DRY 75°C WET, EXPOSED RUN (ER) OR MTW 600V 90°C OR STOOW 105°C 600V - CSA STOOW 600V FT2		
APPROVALS:	UL, c(UL)		