# 1977883-1 ✓ ACTIVE

### AMP | AMP CPC

TE Internal #: 1977883-1

Housing, 600 VDC, Wire-to-Wire, 9 Position, Sealable, Wire &

Cable, Receptacle, Pin, Signal, Black, All Plastic, AMP CPC, Circular

Power Connectors

View on TE.com >



Connectors > Power Connectors > Circular Power > Circular Power Connectors > One-Piece Connector, Sealed, CPC Series 1











Connector Product Type: Housing

Operating Voltage: 600 VDC

Connector System: Wire-to-Wire

Number of Positions: 9

Sealable: Yes

All One-Piece Connector, Sealed, CPC Series 1 (33)

### **Features**

### **Product Type Features**

| Connector Seal & Plug Type        | Peripheral, Wire Entry Seal |
|-----------------------------------|-----------------------------|
| Connector Product Type            | Housing                     |
| Connector System                  | Wire-to-Wire                |
| Sealable                          | Yes                         |
| Connector & Contact Terminates To | Wire & Cable                |
| Connector & Housing Type          | Receptacle                  |
| Circular Connector Shell Type     | All Plastic                 |

### **Configuration Features**

| Reverse Numbering          | Without |
|----------------------------|---------|
| Number of Positions        | 9       |
| Number of Power Positions  | 0       |
| Number of Signal Positions | 9       |



### **Electrical Characteristics**

| Liectrical Characteristics           |                              |
|--------------------------------------|------------------------------|
| Operating Voltage                    | 600 VAC                      |
| Contact Features                     |                              |
| Reverse Gender                       | No                           |
| Contact Type                         | Pin                          |
| Contact Protection                   | With                         |
| Mechanical Attachment                |                              |
| Mating Alignment Type                | Keyed                        |
| Mating Alignment                     | With                         |
| Mating Retention Type                | Threaded Coupling            |
| Thread Size                          | 3/4 - 20 UNEF-2A             |
| Polarization Code                    | A                            |
| Mating Retention                     | With                         |
| Panel Mount Feature                  | Without                      |
| Housing Features                     |                              |
| Body Orientation                     | Straight                     |
| Housing Color                        | Black                        |
| Housing Material                     | Nylon (UV Resistant)         |
| Circular Connector Shell Size        | 13                           |
| Dimensions                           |                              |
| Compatible Insulation Diameter Range | 1.65 – 2.54 mm[.065 – .1 in] |
| Usage Conditions                     |                              |
| Operating Temperature Range          | -55 – 105 °C[-67 – 221 °F]   |
| Fluid Resistance                     | Immersion                    |
| Operation/Application                |                              |
| Circuit Application                  | Signal                       |
| Shielded                             | No                           |
| Industry Standards                   |                              |
| UL Flammability Rating               | UL 94V-0                     |
| Packaging Features                   |                              |
| Packaging Quantity                   | 1                            |
| Packaging Method                     | Package                      |



### **Product Compliance**


For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per<br>homogenous material. Also BFR/CFR/PVC<br>Free                                 |
| Solder Process Capability                     | Not applicable for solder process capability  |

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

### Compatible Parts





















### Also in the Series | AMP CPC




Circular Power Connectors(458)



Connector Backshells(1)



Connector Caps & Covers(19)



Connector Contacts(6)



Connector Hardware(12)




Connector Seals & Cavity Plugs(36)



Connector Strain Relief(60)



Insertion & Extraction Tools(1)



## Customers Also Bought

















### **Documents**

### **Product Drawings**

SLD CPC RCPT ASSY,13-9,STD SEX, UV RESIS

English

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1977883-1\_B.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1977883-1\_B.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1977883-1\_B.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### **Product Specifications**

Connector, Circular Plastic

English

**Product Specification** 

English