

0826543

https://www.phoenixcontact.com/us/products/0826543

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Carrier for conductor marking collar, black, unlabeled, mounting type: Assembly with cable ties, cable diameter: > 16 mm, lettering field size: 100 x 10 mm

Your advantages

- · The printed individual markers are pushed onto the corresponding holders
- · Cable markers for marking cables and conductors with larger cross sections

Commercial data

Item number	0826543
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	BG12
Product key	BG231A
Catalog page	Page 245 (C-3-2019)
GTIN	4046356414517
Weight per piece (including packing)	1.324 g
Weight per piece (excluding packing)	1.276 g
Customs tariff number	39269097
Country of origin	SE



0826543

https://www.phoenixcontact.com/us/products/0826543

Technical data

Product properties

Product type	Marker carrier cable
Туре	Marking strip/label

Dimensions

Width	10 mm
Text field width	100.00 mm
Text field height	10.00 mm
Length	100 mm

External dimensions

Outside diameter	> 16 mm 136 mm
------------------	----------------

Material specifications

Color	black
Material	PVC

Cable/line

External cable diameter	> 16.00 mm

Environmental and real-life conditions

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-1):2011-07 DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl [CAS No. 67-63-0]	Test passed
n-Hexane [CAS No. 110-54-3]	Test passed
Water + Petroleum ether [CAS No. 64742-82-1]	Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

Salt spray test

	Specification	DIN EN 60068-2-11:2000-02



0826543

https://www.phoenixcontact.com/us/products/0826543

Result	Test passed	
Ambient conditions		
Ambient temperature (operation)	-30 °C 70 °C	
Recommended ambient temperature (storage/transport)	23 °C	
Recommended humidity (storage/transport)	50 % (Storage in a dry and dark place in the original packaging is recommended)	
Standards and regulations		
andards and regulations		
andards and regulations Wipe resistance	DIN EN 61010-1 (VDE 0411-1)	
•	DIN EN 61010-1 (VDE 0411-1)	



0826543

https://www.phoenixcontact.com/us/products/0826543

Classifications

ECLASS

	ECLASS-11.0	27281102			
	ECLASS-12.0	27281102			
	ECLASS-13.0	27281102			
ΕΊ	ETIM				
	ETIM 9.0	EC001530			
U	UNSPSC				
	UNSPSC 21.0	39131500			



0826543

https://www.phoenixcontact.com/us/products/0826543

Environmental product compliance

REACH candidate substance (CAS No.)

EU RoHS		
	Fulfills EU RoHS substance requirements	Yes, No exemptions
	EU REACH SVHC	

No substance above 0.1 wt%



0826543

https://www.phoenixcontact.com/us/products/0826543

Accessories

SD-WMTBS (NEUTRAL) CC - Conductor marking collar

0826637

https://www.phoenixcontact.com/us/products/0826637



Conductor marking collar, yellow: without print, mounting type: slide-on, cable diameter: > 16 mm, lettering field size: 4.3×26 mm

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com